Product summary page for Fields X-ray Doorset generated 18.08.2016 by ribaproductselector.com



C W Fields & Son





Fields X-ray Doorset By C W Fields & Son

# **Detailed description**

70 mm robust timber rebated door leaf with lead equivalent 3.6 mm sub faces. The door leaf may be faced with decorative wood veneers, plastic laminates, stains or paints as required. Available as a doorset and can be partnered with Fields Wall Panelling for a fully coordinated design.

#### Features:

- Available Fire Rating FD30, FD60 or non-fire rated.
- Radiation proof vision panels available.
- Single or double door.

#### **Product guidance - As Standard**

Size (maximum):

3250 x 1050 mm.

Thickness:

70 mm.

#### **Options**

#### Performance:

- Radiation shielding performance tested by RRPPS (Radiation Protection Service within the Imaging and Medical Physics Group of University Hospital Birmingham NHS Trust).
- Mechanical test severe duty: DD171.
- Mechanical test severe duty Class 4: EN 947, EN 948, EN 949 and EN 950 (classified to BS EN 1192).
- Mechanical test severe duty Class 8: BS EN 1191 (with classification according to EN 12400): completed 1 000 000 cycles (dependent on configuration).
- Fire resistance test to BS 476-22 by Chiltern International Fire Ltd.

# ribaproductselector.com

Your essential resource for building product information online

# Product summary page for Fields X-ray Doorset generated 18.08.2016 by ribaproductselector.com

#### Glazing:

Radiation proof vision panels are available with a 500 x 200 mm aperture, fixed with hardwood splayed and rebated factory-fitted cloak bead and all necessary fire seals when required.

## Over panels:

One piece over panels not greater than the width of door leaf/ leaves are permitted in all configurations with a separating transom. A rebated or square interface between door leaf and over panel is also permitted without transom. Maximum allowed heights are:

- Single leaves: 2000 mm.
- Double leaves: 1500 mm.

#### Lipping:

All doors will be supplied with hardwood lippings, concealed or exposed and square or rebated.

#### Frame and architraves:

Supplied with a 640 kg/m³ density or greater hardwood of minimum section 122 x 64 mm after rebating or profiling.

## Ironmongery:

Doorsets are machined for 4 Cooke Brothers Loadmaster 7935 stainless steel hinges.

C W Fields & Son

# **Product specification**

Manufacturer

- Name:

- Web:	www.cwfields.co.uk
- Email:	info@cwfields.co.uk
- Tel:	+44 (0)1427 872368
- Fax:	+44 (0)1427 873057
- Address:	Station Road Industrial Estate, Epworth, Doncaster, South Yorkshire DN9 1JZ
Product reference	Fields X-ray Doorset FD30 Fields X-ray Doorset FD60 Fields X-ray Doorset non-fire rated
Size	[]
Glazing	[]
Туре	[]
Size	[]

# ribaproductselector.com

Your **essential resource** for building product information online

Product summary page for Fields X-ray Doorset generated 18.08.2016 by ribaproductselector.com

Shape	
Туре	[]
Size	[]
Shape	[]
Facing	Hygienilac PVC - Antibacterial facing. Laminate - Exposed, concealed over door edges. PVC - Exposed, concealed over door edges. Wood veneer - Book, slip or random matched and laid either vertically or horizontally.
Finish	Clear lacquer Factory painted Final finish - Can be matt or high gloss as required. Primed for onsite painting Stain Tinted lacquer
Ironmongery	