

# XS-IPB830ZSWHA-4P

4Mpx IP PRO Camera

1/3" Progressive CMOS

Compression H.265+ / H.265 /

H.264+ / H.264

Varifocal Motorized Lens 2.7~13.5

mm | WDR

Audio and Alarms| IR LEDs Range 60

m

Weatherproof IP67



X-Security

IP camera

Pro range

1/3" Progressive CMOS

4 Megapixel (2688x1520)

2.7~13.5 mm motorised varifocal autofocus lens

High sensitivity Starlight

0.008 Lux

IR Array Range 60 m

Compression H.265+/H.265/H.264+/H.264

RJ-45 10/100 BaseT

PoE IEEE802.3af

Weatherproof IP67

WDR

IR Cut

SD card recording

Intelligent detection: line crossing, intrusion

WEB Interface, CMS (DSS/ PSS), Smartphone and NVR

ONVIF Compatible

# Specifications

<b>Brand</b>	X-Security
<b>Image sensor</b>	1/3" Progressive CMOS
<b>Maximum resolution</b>	4 Megapixel (2688x1520)
<b>Main Stream rate</b>	4Mpx (1 ~ 20fps)/3M(1 ~ 25/30fps)
<b>Extra Stream rate</b>	D1/CIF(1 ~ 25/30fps)
<b>Compression</b>	H.265+/H.265/H.264+/H.264
<b>Bitrate</b>	H.265: 12K ~ 6400Kbps H.264: 32K ~ 10240Kbps
<b>Lens</b>	2.7~13.5mm motorized HF
<b>Minimum illumination</b>	0.006Lux/F1.4(Color,1/3s,30IRE)
<b>Infrared lighting</b>	0 Lux / IR LEDs Array (60 m)
<b>Image improvements</b>	WDR, Smart IR, BLC, HLC, AWB, AGC, 3D-NR, Privacy Masking, Motion Detection, ROI
<b>Video analysis</b>	Line crossing   Area intrusion
<b>Day / Night</b>	Removable mechanical ICR filter
<b>Network interface</b>	Ethernet 10/100 BaseT
<b>Internal memory</b>	Slot for MicroSD card, Max 128 GB
<b>Remote access</b>	Web browser, CMS Software (DSS/PSS), Smartphone (DMSS) and NVR
<b>Interoperability</b>	ONVIF
<b>Audio</b>	1 Input / 1 Output
<b>Alarms</b>	1 Input / 1 Relay
<b>Power</b>	DC 12 V / 1000 mA, PoE IEEE802.3af
<b>Degree of protection</b>	Weatherproof IP67
<b>Temp. operation</b>	-30° C ~ +60° C
<b>Dimensions</b>	244 mm (Fo) x 79 (An) x 76 (Al) mm
<b>Weight</b>	0.815 Kg