Arioso Wall mounted hood





Features

Designed for ducting out or recycling

- The intelligent ASC system
- Quick release dishwasher proof grease filter
- A convenient filter alarm that tells you when to clean the grease filters for ultimate efficiency
- Suitable for use with back panel
- 2 x halogen lamps 20 watts

When recycling you will require

Recycling charcoal filter - CASS x 1

When ducting out you will require

• Ducting outlet size 150mm (diameter)

Speed	1	2	3	
Air capacity cubic metres per hour*	285	610	700	
Noise level - dbA**	51	66	69	

Energy efficiency	А	В	С	D
Class			•	

Size options

Available in 90cm, 100cm, 110cm or 120cm

Colour options

Stainless steel	Gloss cream	Gloss black	Gloss red

ASC

Advanced Sensor Control

ASC hoods are fitted with a sensor that detects steam, vapours, smoke and odours generated by cooking. This makes the hood fully automatic and no manual intervention is required.

When the sensor no longer detects odours, steam or smoke the hood continues to operate for a further few minutes to ensure all residual odours have been eliminated before turning itself off.

Further features of ASC include:

- The sensitivity level of the ASC System can be easily adjusted to suit your personal needs
- The ASC can temporarily be changed by hand
- The hood can be changed from ASC System to manual operation at the touch of a button
- * Performance data according to Standard EN61591. Free air delivery.
- **Noise level according to Standard IEC60704-2-13 method. All noise level – dbA figures are tested on ducted hoods.