



Neff
D57MH56N0B
Canopy hood

Predecessor:

Successor:

EAN code:
4242004187769

sales programme:

Canopy hood
D57MH56N0B
70 cm wide

Features

- LED display
- 2 x 1W LED lights
- 2 metal grease filter cassettes
- Stainless steel filter cover, metal grease filter
- 3 speeds plus intensive
- Automatic intensive revert (6mins)
- Rim ventilation

Design

- Stainless steel
- Stainless steel with glass canopy
- 70 cm wide Canopy hood
- Standard design
- Soft touch control
- Electronic controls
- Light Colour: warm white

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction charcoal filter (accessory) needed
- Twin channel high performance fan motor
- In recirculation operation chimless use possible
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 630 m³/h
Intensive 730 m³/h
- Power rating: 277 W
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 66 dB (A) re 1pW
- Noise max. Normal Level: 66 dB*
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Electrical cable length 1.5 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 418-418 x 700 x 300 mm
- Dimensions recirculating (HxWxD): 418-418 x 700 x 300 mm
- Energy Efficiency Class: C*
- Blower Efficiency Class: C*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*
- Average Energy Consumption: 105.7 kWh/year*

Optional accessories

- Recirculating kit

Included accessories

Optional accessories

Alternative colors available

Technical Data

Characteristics

Typology : Traditional
Approval certificates : CE, VDE
Length of electrical supply cord (cm) : 150
Required niche size for installation (HxWxD) : 418mm x 676mm x 264mm
Minimum distance above an electric hob : 500
Minimum distance above a gas hob : 650
Net weight (kg) : 9.0
Type of control : Electronic
Number of speed settings : 3
Maximum output air extraction (m3/h) : 630
Boost position output recirculating (m3/h) : 310
Maximum output recirculating air (m3/h) : 300
Boost position air extraction (m³/h) : 730
Number of lights (Stck) : 2
Noise level (dB(A) re 1 pW) : 66
Diameter of air outlet (mm) : 120 / 150
Grease filter material : Washable aluminium
EAN code : 4242004187769

Consumption and connection features

Connection rating (W) : 277
Current (A) : 3
Voltage (V) : 220-240
Frequency (Hz) : 50
Plug type : GB plug
Installation type : Half-integrated