

Data sheet for household cooker hoods

In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele			
Model name / identifier		DA 1260	
Annual Energy Consumption (AEC) (AEC_{Haube})	kWh/year	91,6	
Energy efficiency class		C	
Based on standard test results for 24 hours. Actual energy consumption will depend on how the appliance is used and where it is located.			
Energy efficiency index (EEI) (EEI_{Haube})		82,1	
Fluid Dynamic Efficiency (FDE) (FDE_{Haube})		16,3	
Fluid Dynamic Efficiency class		D	
A (most efficient) to G (least efficient)			
Lighting Efficiency (LE) (LE_{Haube})	lx/W	55,0	
Lighting Efficiency class		A	
A (most efficient) to G (least efficient)			
Grease Filtering Efficiency	%	95,1	
Grease Filtering Efficiency class		A	
A (most efficient) to G (least efficient)			
Airflow at best efficiency point	m ³ /h	317,1	
Air flow (min. speed)	m ³ /h	275	
Air flow (max. speed)	m ³ /h	355	
Air flow (intensive or boost setting)	m ³ /h	545	
Max. air flow (Q) (Q_{max})	m ³ /h	545	
Air pressure at best efficiency point	Pa	313	
Airborne acoustical A-weighted sound power emissions (min. speed)	dB	57	
Airborne acoustical A-weighted sound power emissions (max. speed)	dB	64	
Airborne acoustical A-weighted sound power emissions (intensive or boost setting)	dB	74	
Electrical power input at best efficiency point	W	169,0	
Power consumption in off mode (P_o)	W	0,00	
Power consumption in standby mode (P_s)	W		
Nominal power of lighting system	W	6,0	
Average illumination of the lighting system on the cooking surface	lx	330	
Time increase factor		1,4	