

## INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:	IECEx BKI 07.0034		Issue No: 2	Certificate history:
Status:	Current		Page 1 of 4	Issue No. 2 (2012-02-13) Issue No. 1 (2011-09-19)
Date of Issue:	2012-02-13			Issue No. 0 (2007-10-02)
Applicant:	Cooper Crouse-Hinds GmbH previously CEAG Sicherheitstechni Neuer Weg Nord 49 D-69412 Eberbach, Germany Germany	k GmbH		
Electrical Apparatus:	Junction boxes and terminal boxes			
Optional accessory:	Type GHG 791 01 and 791 02			
Type of Protection:	General requirements, Increased sa	afety, Intrinsic safety, D	ust explosion prot	ection
Marking:	Ex e II T6 for non intrinsically safe of Ex ia IIC T6 for intrinsically safe circ -50 °C ≤ Tamb ≤ +45 °C Ex tD A21 IP66 T58°C	circuits only cuits only		
Approved for issue on behalf of the Certification Body:	e IECEx	János FEJES		
Position:		Director		
Signature: (for printed version)				
Date:	-			
	-			
<ol> <li>This certificate and schedule may only be reproduced in full.</li> <li>This certificate is not transferable and remains the property of the issuing body.</li> <li>The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.</li> </ol>				
Certificate issued by:				
Testing Station for Explosion Proof Equipment H 1037 BUDAPEST MIKOVINY S.u. 2-4 Hungary				



Issue No: 2

Page 2 of 4

Certificate No:	IECEx BKI 07.0034
Date of Issue:	2012-02-13
Manufacturer:	Cooper Crouse-Hinds GmbH Neuer Weg Nord 49 D-69412 Eberbach, Germany Germany

Additional Manufacturing location(s):

S.C. Cooper Industries Romania S.R.L. Zona Industrial NV Str. III, No. 12 ARAD, Romania

Romania

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

### STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2004 Edition:4.0	Electrical apparatus for explosive gas atmospheres - Part 0: General requirements
IEC 60079-11 : 1999 Edition:4	Electrical apparatus for explosive gas atmospheres - Part 11: Intrinsic safety 'i'
IEC 60079-7 : 2001 Edition:3	Electrical apparatus for explosive gas atmospheres - Part 7: Increased safety 'e'
IEC 61241-0 : 2004 Edition:1	Electrical apparatus for use in the presence of combustible dust - Part 0: General requirements
IEC 61241-1 : 2004 Edition:1	Electrical apparatus for use in the presence of combustible dust - Part 1: Protection by enclosures "tD"

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the

Standards listed above.

### TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:

HU/BKI/ExTR07.0033/00

Quality Assessment Report:

DE/BVS/QAR11.0006/01

DE/BVS/QAR11.0009/00

HU/BKI/QAR06.0005/01



Certificate No:

IECEx BKI 07.0034

Issue No: 2

Date of Issue:

2012-02-13

Page 3 of 4

Schedule

### EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

Junction boxes and terminal boxes made of polyamide of types GHG 791 01 and 791 02, intended for permanent installation, with built-in moduler or mantle terminals for non-intrinsically safe and intrinsically safe (certified separatly) circuits.

See details in Addendum to IECEx BKI 07.0034.

CONDITIONS OF CERTIFICATION: NO



Issue No: 2

Page 4 of 4

Certificate No:

IECEx BKI 07.0034

2012-02-13

Date of Issue:

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

New manufacturing location: S.C. Cooper Industries Romania S.R.L.

Address: Zona Industrial NV, str. III, No. 12

ARAD, Romania

### Annex:

Addendum to IECEx BKI 07.0034.pdf



## ADDENDUM TO IECEX CERTIFICATE OF CONFORMITY IECEX BKI 07.0034

#### 1. Description

Junction boxes and terminal boxes made of polyamide of types GHG 791 01 and 791 02, intended for permanent installation, with built-in moduler or mantle terminals for non-intrinsically safe and intrinsically safe (certified separatly) circuits.

The junction boxes and terminal boxes, of type GHG 791 01 and 791 02 may now also be used in areas that have to expected to be occasionally exposed to potentially explosive atmospheres with dust/air mixtures.

The junction boxes and terminal boxes of types GHG 791 01 and 791 02 may optionally be provided with cable entry size M25 or M32, with long screw thread.

The junction boxes and terminal boxes of types GHG 791 01 and 791 02 may be provided with an outside earthing terminal. The companion sheet version for determination of the maximum number of conductors for each enclosure size as function cross section and the permissible continuous current may optionally.

Code for manufacturer

#### 2. Type assortment

GHG 79. ....R.... Legend of the signs from left to right

9.\_, 10.\_, 11.\_, 12.\_, 13.\_, 14.\_, 15.\_

1.\_, 2.\_, 3.\_, 4.\_, 5.\_

6		

7.\_, 8.\_

Type of enclosure (material) 1 = polyamide 2 = stainless steel 3 = aluminium
Box size
Serial number with no influence on Ex-protection

#### 3. General parameters

Rated voltage: maximally 750 V (depending on the working voltage of the terminals used) For terminal boxes have been specified rated current, number of conductors and conductor cross section in the supplementary sheets. Junction boxes GHG 791 01 and 791 02:

Rated cross section, max.:	2.5 mm <sup>2</sup>	4.0 mm <sup>2</sup>	6.0 mm <sup>2</sup>
Rated current, max.:	22 A	30 A	39 A

#### 4. Ambient temperature

Ambient temperature range, normal if EPDM gaskets are used: $-20 \text{ °C} \leq \text{Tamb} \leq +45 \text{ °C}$ Extended ambient temperature range if silicon gaskets are used: $-50 \text{ °C} \leq \text{Tamb} \leq +45 \text{ °C}$ 

4.1 Temperature class T6 surface temperature 58 °C

5. Ingress protection IP66 to IEC 60529

#### Note for manufacture and operation

The degree of protection – at least IP 66 – will be reached only by adequate use of the separately tested gaskets, cable and conduit entries and sealing plugs.

Suitability for low ambient temperatures is indicated by separate marking. Only, such gaskets and attachments which are suitable for these temperatures and for which a separate certificate has been issued. Further notes of the manufacturer are to be taken into account.

For the maximum number of conductors for each enclosure size, which is subject to the cross section and the permissible continuous current, reference is made to the attached date sheets.

The cable entry shall be glued in place by means of adhesive DELOPUR 9693 or 9694.



## ADDENDUM TO IECEX CERTIFICATE OF CONFORMITY IECEX BKI 07.0034

**Page** 2 of 2

Drawing	
Description Nr. 4252, 3 pages	20.04.2000
List of materials, 2 pages	20.04.2000
Drawing No. GHG 79-1-3916	20.04.2000
GHG 79101 in acc. with Enclosure 1, 1 page	20.04.2000
GHG 79102 in acc. with Enclosure 2, 1 page	20.04.2000
PTB test protocol on impact test (+55 °C; -45 °C)	21.02.1996
PTB test protocol on impact test (-55 °C)	21.02.1996
PTB test protocol on test of degree of protection (IPX4)	21.02.1996
PTB test protocol "Current heat rise at terminals" (pillar terminals)	01-04.04.1996
PTB test protocol "Current heat rise at terminals" (row terminals) 791 01	28-31.05.1996
PTB test protocol "Current heat rise at terminals" (row terminals) 791 02	03-06.06.1996
PTB test protocol on determination of electrical conductivity	14.06.2000
PTB test protocol "Test of earth connection through non-metal enclosures"	03.07.2000
CEAG-test protocol on pull test of cable entries and test of degree of protection	29.02.2000
Data sheet "Non-metallic enclosures and enclosure parts" on Vestamide L-R7-MHI, black,	
from Messrs. Creanova Spezialchemie, 5 pages	25.05.1998
Data sheet "Non-metallic enclosures and enclosure parts" on Ultramide A3Z	
from Messrs. BASF AG, 2 pages	14.03.2000
Data sheet "Non-metallic enclosures and enclosure parts" on Ultramide A3XZ G5	
from Messrs. BASF AG, 3 pages	14.03.2000
Data sheet "Non-metallic enclosures and enclosure parts" on Hostaform C 13031	
from Messrs. Ticona GmbH, 3 pages	14.03.2000
Data sheet "Elastomer parts and seal" on Fermasil A/B 33 and A/B 38 from	
Messrs. Erich Sonderhoff GmbH & Co. KG, 11 pages	01.03.2000
PTB letter on usability of "Fermasil A 38-2 seal, Messrs. Sonderhoff GmbH & Co. KG"	01.09.1997
Operating instructions Ex-terminal boxes GHG 791 01, 791 02	20.04.2000
Operating instructions Ex-junction boxes GHG 791 01, 791 02	20.04.2000
Test Report PTB Ex 00-30059, 7 pages	03.07.2000
1. Supplement Descriptive documents	
Description Nr. 4252 1. Supplement, 1 page	2001-07-06
Test protocol of DMT No. BVS PP 01-2070 EG dated	2001-06-25
Test Report PTB Ex 01-11176, 2 pages	26.07.2001
2. Supplement Descriptive documents	
Description No. 4252 2. Supplement, 3 pages	2001-12-01
Enclosure No. 3, 1 page	2001-12-01
Drawing No. GHG / 9-3-4368, 1 page	2001-12-01
Test Report PTB Ex 01-11317, 2 pages	2002.02.11.
3. Supplement Descriptive documents	
Description No. 4252 3. Supplement, 1 page	2002-08-02
lest protocol No. 01-M14-B1-160/02	
Date sheet of addresive DELO-POR 9693	
lest Report PIB Ex 02-12279, 2 pages	2002.09.13.
4. Supplement Descriptive documents	0004 00 40
Description No 4252 4. Supplement, 1 page	2004-03-16
Test report No. 0 I-MI4-B I-03032004	
Data sneet, adnesive DELO-POR 9694	0004.04.00
lest Report PTB 04-14087, 2 pages	2004.04.28.
5. Supplement Descriptive documents	2004 00 42
Description No. 4252 5. Supplement, 2 pages	2004.09.13.
GHG 79101 in acc with Enclosure 1 variant, 1 page	2004.09.13.
Group No. CHC 200.4.4442	2004.09.13.
	2004.04.20.
	2004.09.13.
	2004.04.20.
Checkenser Celocity in 1, March 1, 106082004, 3 pages	2004 08 06
Test Report CEAC No. 0.1-MI4-B1-18082004, 3 pages	2004.00.00
Test Penort DTR N 25/00 1 nage	2004.00.10. 2000 07 02
Test Report Cooper Crouse-Hinds - EvVA BKI Nr. 04-MM-18042006 5 pages	2000.07.03.
Test Report Cooper Crouse-Hinds – ExVA BKI Nr. 03-MI4-18042000, 5 pages	2000.03.02.
PTB letter about the highest temperature	2000.00.02.
· · · · · · · · · · · · · · · · · · ·	2000.00.00.