

KEY:

PARTITIONS

Please refer to Specification BIP-MLA-XX-XX-SP-A-220
Plasterboard Partitions, Linings & Ceilings

BLOCKWORK

B1 - Refer to Spec Ref: BIP-MLA-XX-XX-SP-A-223 - Masonry Walling - concrete
blockwork Ss_25_13_50_56

PLASTERBOARD PARTITIONS

P1 - Refer to Spec Ref: Ss_25_10_30_35 - Partition Type P1

P2 & P2.A - Refer to Spec Ref: Ss_25_10_30_35 - Partition Type P2 and P2.A

P3 & P3.A - Refer to Spec Ref: Ss_25_10_30_35 - Partition Type P3 / P3.A / P3B

P4 - Refer to Spec Ref: Ss_25_10_30_35 - Partition Type P4

WALL LININGS

L1 & L1.A - Refer to Spec Ref: Ss_25_25_45_35 Lining Type

L2 - Refer to Spec Ref: Ss_25_25_45_35 Lining Type

L3 - Refer to Spec Ref: Ss_25_25_45_35 Lining Type to external envelope.
Dash magenta line refer to L3 at low level under curtain walling and from level
01 slab to top of the gables at the 2no. side internal elevations.

PATITRESS

Blue line denotes location of Plywood Pattress to Partition or Lining

GLAZED PARTITIONS

G1 - Refer to Spec Ref: Ss_25_12_65_65 - Type G1

G2 - Refer to Spec Ref: Ss_25_12_65_65 - Type G2

1t

Indicates non-fire rated
partition type

1t
1hr

Indicates fire rated
partition type

NOTE

Partitions to achieve a minimum
acoustic rating of 45dB.
Current partition specifications are
defined by the British Gypsum
standard height table. Soffit
Deflection TBC by Structural
Engineer

WALL FINISHES: Please refer to Specification BIP-MLA-XX-XX-SP-A-421
A-421
Decoration and Internal wall Finishes.

WT1: All walls to be paint finish Ss_40_90_60_05
* For wall finishes at wet/wc's refer to (74) series drawings.

SKIRTINGS: Please refer to Specification BIP-MLA-XX-XX-SP-A-700

Joinery

Allow for planted on timber skirtings throughout. Pr_35_90_43_98
*For skirting in wet/ wc areas refer to (74) series drawings.

