



REV	BY	DATE	DESCRIPTION
A	.	.	FIRST ISSUE

PARTITION TYPES	
EXISTING PARTITION	DENOTED EXISTING CORE WALL OR PARTITION TO REMAIN
NEW PARTITION	100MM - SINGLE 12.5MM PLASTERBOARD TO BOTH SIDES OF A 70MM METAL STUD. 50MM ROCKWOOL INFILL.
NOTE: ALL NEW PARTITION ARE BUILT FROM RAISED FLOOR TO SUSPENDED CEILING UNLESS STATED	

PARTITION INFORMATION	
NEW FULL HEIGHT PARTITION	PARTITION BUILT FULL HEIGHT - FROM SLAB TO STRUCTURAL SOFFIT UNLESS STATED
NEW ACOUSTIC BARRIER OVER	CEILING VOID OVER PARTITION TO HAVE ACOUSTIC BARRIER INSTALLED
NEW 1/2 HOUR FIRE RATED PARTITION	PARTITION ENCLOSURE IS FIRE RATED TO 30 MINUTES. FIRE BARRIER TO FLOOR & CEILING VOID IF APPLICABLE
NEW PLY LINING	NEW PARTITION STRENGTHENED WITH 12MM PLY INTERNAL LINING TO ONE SIDE

GLAZING	
NEW STRUCTURAL GLAZING	SILICON JOINTED 'FRAMELESS' GLAZING
NEW FRAMED GLAZING MODULE	METAL FRAMED DOUBLE GLAZED SYSTEM. HEIGHT TO MATCH NEW DOOR SETS

SYMBOLS	
DOORS	
ET-10	DOOR No. (EXT'G DOORS)
VP	VISION PANEL
FD30S	30 MIN FIRE RATED DOOR
FD60S	60 MIN FIRE RATED DOOR

MODUS:

Gordon House
Greencoat Place
London SW1P 1PH

T: +44 20 7828 9009
Info@modusgroup.com
www.modusgroup.com

CLIENT:
MACROSYNERGY

SITE ADDRESS:
**MELBOURNE HOUSE
LONDON WC2**

DRAWING TITLE:
**GENERAL ARRANGEMENT
???? FLOOR**

SCALE: 1:100@A1
DRAWN BY: WAI WAN
CHECKED BY:
DATE: 2015-3-24

JOB No.	TYPE	BLG.	SERIES	FLOOR	REV.
1707W	GA	1	1	00	A

FOR COMMENT