

# Y3449F\_A9

## Safety Data Sheet ULTRA RED



Bulk Sales Reference No.:  
SDS Revision Date:  
SDS Revision Number:

Sales  
Order: {SalesOrd}  
Y3449F  
03/15/2017  
A9-5

### 1. Identification of the preparation and company

#### 1.1. Product identifier

Product Identity ULTRA RED  
Bulk Sales Reference No. Y3449F

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.  
Application Method See Technical Data Sheet.

#### 1.3. Details of the supplier of the safety data sheet

Company Name Akzo Nobel Coatings  
International Paint LLC  
6001 Antoine Drive  
Houston, TX 77095

#### Emergency

CHEMTREC (USA) (800) 424-9300  
International Paint (713) 527-3887  
Poison Control Center (800) 854-681  
Customer Service  
International Paint (800) 589-1267  
Fax No. (800) 631-7481

### 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.  
Acute Tox. 4;H302 Harmful if swallowed.  
Acute Tox. 5;H313 May be harmful in contact with skin.  
Skin Irrit. 2;H315 Causes skin irritation.  
Eye Irrit. 2;H319 Causes serious eye irritation.  
Skin Sens. 1;H317 May cause an allergic skin reaction.  
Aquatic Chronic 1;H410 Very toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Danger.

H226 Flammable liquid and vapor.  
H302 Harmful if swallowed.  
H313 May be harmful in contact with skin.

## Y3449F\_A9

- H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H410 Very toxic to aquatic life with long lasting effects.
- P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.  
 P235 Keep cool.  
 P240 Ground / bond container and receiving equipment.  
 P241 Use explosion-proof electrical / ventilating / light / equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P260 Do not breathe mist / vapors / spray.  
 P261 Avoid breathing dust / fume / gas / mist / vapors / spray.  
 P262 Do not get in eyes, on skin, or on clothing.  
 P270 Do not eat, drink or smoke when using this product.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves / eye protection / face protection.  
 P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
 P302+352 IF ON SKIN: Wash with soap and water.  
 P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.  
 P312 Call a POISON CENTER or doctor / physician if you feel unwell.  
 P330 Rinse mouth.  
 P331 Do NOT induce vomiting.  
 P333+313 If skin irritation or a rash occurs: Get medical advice/attention.  
 P337 If eye irritation persists:..  
 P362 Take off contaminated clothing and wash before reuse.  
 P363 Wash contaminated clothing before reuse.  
 P370 In case of fire: Use water spray, fog, or regular foam..  
 P391 Collect spillage.  
 P403+233 Store in a well ventilated place. Keep container tightly closed.  
 P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating                      Health: 2\*                      Flammability: 3                      Reactivity: 0

|   |
|---|
| 3. Composition/information on ingredients |
|---|

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations                             | Weight % | GHS Classification   | Notes  |
|--|----------|--|--------|
| Copper oxide (Cu <sub>2</sub> O)<br>CAS Number: 0001317-39-1 | 50 - 75  | Acute Tox. 4;H302<br>Aquatic Acute 1;H400<br>Aquatic Chronic 1;H410  | [1]    |
| Xylenes (o-, m-, p- isomers)<br>CAS Number: 0001330-20-7     | 10 - 25  | Flam. Liq. 3;H226<br>Acute Tox. 4;H332<br>Acute Tox. 4;H312<br>Skin Irrit. 2;H315<br>Eye Irrit. 2;H319<br>STOT SE 3;H335<br>Asp. Tox. 1;H304 | [1][2] |
| Rosin<br>CAS Number: 0008050-09-7                            | 1.0 - 10 | Skin Sens. 1;H317  | [1]    |
| Zinc oxide<br>CAS Number: 0001314-13-2                       | 1.0 - 10 | Aquatic Acute 1;H400<br>Aquatic Chronic 1;H410   | [1][2] |

## Y3449F\_A9

|  |          |   |        |
|--|----------|---|--------|
| Glass, oxide, chemicals<br>CAS Number: 0065997-17-3                            | 1.0 - 10 | ----  | [1]    |
| Iron oxide<br>CAS Number: 0001309-37-1   | 1.0 - 10 | ----  | [1][2] |
| Benzene, ethyl-<br>CAS Number: 0000100-41-4                                    | 1.0 - 10 | Flam. Liq. 2;H225<br>Acute Tox. 4;H332<br>Asp. Tox. 1;H304<br>Eye Irrit. 2;H319<br>Skin Irrit. 2;H315<br>STOT SE 3;H335<br>STOT RE 2;H373 | [1][2] |
| Copper oxide<br>CAS Number: 0001317-38-0                                       | 1.0 - 10 | ----  | [1]    |
| Barium sulfate<br>CAS Number: 0007727-43-7                                     | 1.0 - 10 | ----  | [1][2] |
| Copper<br>CAS Number: 0007440-50-8   | 1.0 - 10 | Flam. Sol. 2;H228<br>Acute Tox. 4;H332<br>Acute Tox. 4;H302<br>Aquatic Acute<br>1;H400 (Supplier<br>Classification)                       | [1][2] |
| BUTYL-N-CYCLOPROPYL-6-(METHYLTHIO)-1,3,5-TRIAZINE-<br>CAS Number: 0028159-98-0 | 1.0 - 10 | Skin Sens. 1;H317<br>Aquatic Chronic<br>1;H410  | [1]    |

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

### 4. First aid measures

#### 4.1. Description of first aid measures

|            |   |
|------------|---|
| General    | Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.  |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.  |
| Eyes       | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.   |
| Skin       | In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.  |
| Ingestion  | If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. |

#### 4.2. Most important symptoms and effects, both acute and delayed

|                 |  |
|-----------------|--|
| Overview        | NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. |
| Inhalation      | Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.  |
| Eyes            | Causes severe eye irritation. Avoid contact with eyes.   |
| Skin            | Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin.   |
| Ingestion       | Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.   |
| Chronic effects | Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.   |

### 5. Fire-fighting measures

#### 5.1. Extinguishing media

## Y3449F\_A9

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. SMALL FIRES: Use dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam. LARGE FIRES: Use water spray, fog, or alcohol-resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

### 5.2. Special hazards arising from the substance or mixture

May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

### 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No.

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

### 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

### 6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

## 7. Handling and storage

### 7.1. Precautions for safe handling

Handling

Vapors may cause flash fire or ignite explosively.

In Storage

Keep away from heat, sparks and flame.

### 7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

### 7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

## 8. Exposure controls and personal protection

### 8.1. Control parameters

Exposure

| CAS No.      | Ingredient      | Source | Value  |
|--------------|-----------------|--------|--|
| 0000100-41-4 | Benzene, ethyl- | OSHA   | 100 ppm TWA; 435 mg/m <sup>3</sup> TWA125 ppm STEL; 545 mg/m <sup>3</sup> STEL |
|              |                 | ACGIH  | 20 ppm TWA   |

Y3449F\_A9

|              |            |           |  |
|--------------|------------|-----------|--|
|              |            | NIOSH     | 100 ppm TWA; 435 mg/m <sup>3</sup> TWA125 ppm STEL; 545 mg/m <sup>3</sup> STEL800 ppm IDLH (10% LEL)   |
|              |            | Supplier  |  |
|              |            | OHSA, CAN | 20 ppm TWA   |
|              |            | Mexico    | 100 ppm TWA LMPE-PPT; 435 mg/m <sup>3</sup> TWA LMPE-PPT125 ppm STEL [LMPE-CT]; 545 mg/m <sup>3</sup> STEL [LMPE-CT]                                 |
|              |            | Brazil    | 78 ppm TWA LT; 340 mg/m <sup>3</sup> TWA LT  |
| 0001309-37-1 | Iron oxide | OSHA      | 10 mg/m <sup>3</sup> TWA (fume); 15 mg/m <sup>3</sup> TWA (total dust, listed under Rouge); 5 mg/m <sup>3</sup> TWA (respirable fra                  |
|              |            | ACGIH     | 5 mg/m <sup>3</sup> TWA (respirable fraction)  |
|              |            | NIOSH     | 5 mg/m <sup>3</sup> TWA (dust and fume, as Fe)2500 mg/m <sup>3</sup> IDLH (dust and fume, as Fe)   |
|              |            | Supplier  |  |
|              |            | OHSA, CAN | 5 mg/m <sup>3</sup> TWA (respirable)   |
|              |            | Mexico    | 5 mg/m <sup>3</sup> TWA LMPE-PPT10 mg/m <sup>3</sup> STEL [LMPE-CT] (as Fe)  |
|              |            | Brazil    |  |
| 0001314-13-2 | Zinc oxide | OSHA      | 5 mg/m <sup>3</sup> TWA (fume); 15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)10 mg/m <sup>3</sup> STEL (fume) |
|              |            | ACGIH     | 2 mg/m <sup>3</sup> TWA (respirable fraction)10 mg/m <sup>3</sup> STEL (respirable fraction)   |
|              |            | NIOSH     | 5 mg/m <sup>3</sup> TWA (dust and fume)10 mg/m <sup>3</sup> STEL (fume)15 mg/m <sup>3</sup> Ceiling (dust)500 mg/m <sup>3</sup> IDLH                 |
|              |            | Supplier  |  |
|              |            | OHSA, CAN | 2 mg/m <sup>3</sup> TWA (respirable)10 mg/m <sup>3</sup> STEL (respirable)   |
|              |            | Mexico    | 5 mg/m <sup>3</sup> TWA LMPE-PPT (fume); 10 mg/m <sup>3</sup> TWA  |

Y3449F\_A9

|              |                              |           |  |
|--------------|------------------------------|-----------|--|
|              |                              |           | LMPE-PPT (dust)10 mg/m3 STEL<br>[LMPE-CT] (fume)   |
|              |                              | Brazil    |  |
| 0001317-38-0 | Copper oxide                 | OSHA      |  |
|              |                              | ACGIH     |  |
|              |                              | NIOSH     | 0.1 mg/m3 TWA (fume, as Cu)  |
|              |                              | Supplier  |  |
|              |                              | OHSA, CAN |  |
|              |                              | Mexico    |  |
|              |                              | Brazil    |  |
| 0001317-39-1 | Copper oxide (Cu2O)          | OSHA      |  |
|              |                              | ACGIH     |  |
|              |                              | NIOSH     |  |
|              |                              | Supplier  |  |
|              |                              | OHSA, CAN |  |
|              |                              | Mexico    |  |
|              |                              | Brazil    |  |
| 0001330-20-7 | Xylenes (o-, m-, p- isomers) | OSHA      | 100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL                                       |
|              |                              | ACGIH     | 100 ppm TWA150 ppm STEL  |
|              |                              | NIOSH     |  |
|              |                              | Supplier  |  |
|              |                              | OHSA, CAN | 100 ppm TWA150 ppm STEL  |
|              |                              | Mexico    | 100 ppm TWA LMPE-PPT; 435 mg/m3 TWA LMPE-PPT150 ppm STEL [LMPE-CT]; 655 mg/m3 STEL [LMPE-CT] |
|              |                              | Brazil    | 78 ppm TWA LT; 340 mg/m3 TWA LT  |
| 0007440-50-8 | Copper                       | OSHA      | 0.1 mg/m3 TWA (fume); 1 mg/m3 TWA (dust and mist)  |
|              |                              | ACGIH     | 0.2 mg/m3 TWA (fume)   |
|              |                              | NIOSH     | 1 mg/m3 TWA (dust and mist); 0.1 mg/m3 TWA (fume)100 mg/m3 IDLH (dust, fume and mist)        |
|              |                              | Supplier  |  |
|              |                              | OHSA, CAN | 0.2 mg/m3 TWA (fume); 1 mg/m3 TWA (dust and mist)  |
|              |                              | Mexico    | 0.2 mg/m3 TWA LMPE-PPT (fume, as Cu); 1 mg/m3 TWA LMPE-PPT (dust and mist, as                |

Y3449F\_A9

|              |  |           |  |
|--------------|--|-----------|--|
|              |  |           | Cu)2 mg/m3 STEL [LMPE-CT] (fume, as Cu); 2 mg/m3 STEL [LMPE-CT] (dust and mist, as Cu) |
|              |  | Brazil    |  |
| 0007727-43-7 | Barium sulfate                                     | OSHA      | 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)                           |
|              |  | ACGIH     | 10 mg/m3 TWA   |
|              |  | NIOSH     | 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)                               |
|              |  | Supplier  |  |
|              |  | OHSA, CAN | 10 mg/m3 TWA   |
|              |  | Mexico    |  |
|              |  | Brazil    |  |
| 0008050-09-7 | Rosin  | OSHA      |  |
|              |  | ACGIH     |  |
|              |  | NIOSH     |  |
|              |  | Supplier  |  |
|              |  | OHSA, CAN | exposure by all routes should be carefully controlled to levels as low as possible     |
|              |  | Mexico    | 0.1 mg/m3 TWA LMPE-PPT (as Formaldehyde)   |
|              |  | Brazil    |  |
| 0028159-98-0 | BUTYL-N-CYCLOPROPYL-6-(METHYLTHIO)-1,3,5-TRIAZINE- | OSHA      |  |
|              |  | ACGIH     |  |
|              |  | NIOSH     |  |
|              |  | Supplier  |  |
|              |  | OHSA, CAN |  |
|              |  | Mexico    |  |
|              |  | Brazil    |  |
| 0065997-17-3 | Glass, oxide, chemicals                            | OSHA      |  |
|              |  | ACGIH     |  |
|              |  | NIOSH     |  |
|              |  | Supplier  |  |
|              |  | OHSA, CAN |  |
|              |  | Mexico    |  |
|              |  | Brazil    |  |

Health Data

| CAS No.      | Ingredient                   | Source | Value                                  |
|--------------|------------------------------|--------|--|
| 0000100-41-4 | Benzene, ethyl-              | NIOSH  | Eye skin                               |
| 0001309-37-1 | Iron oxide                   | NIOSH  | Benign pneumoconiosis termed siderosis |
| 0001314-13-2 | Zinc oxide                   | NIOSH  | Metal fume fever                       |
| 0001317-38-0 | Copper oxide                 | NIOSH  |  |
| 0001317-39-1 | Copper oxide (Cu2O)          | NIOSH  |  |
| 0001330-20-7 | Xylenes (o-, m-, p- isomers) | NIOSH  |  |

Y3449F\_A9

|              |  |       |   |
|--------------|--|-------|---|
|              |  |       | Central nervous system depressant; respiratory and eye irritation |
| 0007440-50-8 | Copper   | NIOSH | Upper respiratory irritation                                      |
| 0007727-43-7 | Barium sulfate                                     | NIOSH | Eye nose  |
| 0008050-09-7 | Rosin  | NIOSH |   |
| 0028159-98-0 | BUTYL-N-CYCLOPROPYL-6-(METHYLTHIO)-1,3,5-TRIAZINE- | NIOSH |   |
| 0065997-17-3 | Glass, oxide, chemicals                            | NIOSH |   |

Carcinogen Data

| CAS No.      | Ingredient   | Source | Value   |
|--------------|--|--------|---|
| 0000100-41-4 | Benzene, ethyl-                                    | OSHA   | Select Carcinogen: Yes  |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0001309-37-1 | Iron oxide   | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0001314-13-2 | Zinc oxide   | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0001317-38-0 | Copper oxide                                       | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0001317-39-1 | Copper oxide (Cu2O)                                | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0001330-20-7 | Xylenes (o-, m-, p- isomers)                       | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0007440-50-8 | Copper   | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0007727-43-7 | Barium sulfate                                     | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0008050-09-7 | Rosin  | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0028159-98-0 | BUTYL-N-CYCLOPROPYL-6-(METHYLTHIO)-1,3,5-TRIAZINE- | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   |   |



Y3449F\_A9

|              |                         |      |  |
|--------------|-------------------------|------|--|
|              |                         |      | Group 1: No; Group 2a: No;<br>Group 2b: No; Group 3: No;<br>Group 4: No; |
| 0065997-17-3 | Glass, oxide, chemicals | OSHA | Select Carcinogen: No  |
|              |                         | NTP  | Known: No; Suspected: No   |
|              |                         | IARC | Group 1: No; Group 2a: No;<br>Group 2b: No; Group 3: No;<br>Group 4: No; |

8.2. Exposure controls

|                      |   |
|----------------------|---|
| Respiratory          | Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet. |
| Eyes                 | Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.  |
| Skin                 | Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.   |
| Engineering Controls | Depending on the site-specific conditions of use, provide adequate ventilation.   |
| Other Work Practices | Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.  |

|                                     |
|-------------------------------------|
| 9. Physical and chemical properties |
|-------------------------------------|

|   |  |
|---|--|
| Appearance                                      | Coloured Liquid  |
| Odour threshold                                 | Not Measured   |
| pH  | No Established Limit   |
| Melting point / freezing point                  | Not Measured   |
| Initial boiling point and boiling range         | 137 (°C) 279 (°F)  |
| Flash Point                                     | 27 (°C) 80 (°F)  |
| Evaporation rate (Ether = 1)                    | Not Measured   |
| Flammability (solid, gas)                       | Not Applicable   |
| Upper/lower flammability or explosive limits    | Lower Explosive Limit: .6<br>Upper Explosive Limit: No Established Limit   |
| vapor pressure (Pa)                             | Not Measured   |
| Vapor Density                                   | Heavier than air   |
| Specific Gravity                                | 2.23   |
| Solubility in Water                             | Not Measured   |
| Partition coefficient n-octanol/water (Log Kow) | Not Measured   |
| Auto-ignition temperature                       | Not Measured   |
| Decomposition temperature                       | Not Measured   |
| Viscosity (cSt)                                 | No Established Limit Not Measured  |
| VOC %   | Refer to the Technical Data Sheet or label where information is available. |
| VOHAP content (gm/litre of paint)               | 500.68 (as supplied)   |

## Y3449F\_A9

VOHAP content (gm/litre of Solid Coating) 321.37 (as supplied)

### 10. Stability and reactivity

**10.1. Reactivity**

No data available

**10.2. Chemical stability**

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

**10.3. Possibility of hazardous reactions**

No data available

**10.4. Conditions to avoid**

No data available

**10.5. Incompatible materials**

Strong oxidizing agents.

**10.6. Hazardous decomposition products**

May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

### 11. Toxicological information

**Acute toxicity**

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

| Ingredient                                 | Oral LD50,<br>mg/kg                    | Skin LD50,<br>mg/kg                       | Inhalation<br>Vapor LD50,<br>mg/L/4hr | Inhalation<br>Dust/Mist LD50,<br>mg/L/4hr |
|--|--|---|---------------------------------------|---|
| Copper oxide (Cu2O) - (1317-39-1)          | 470.00, Rat<br>- Category:<br>4        | 2,000.00,<br>Rabbit -<br>Category: 4      | No data<br>available                  | 50.00, Rat -<br>Category: NA              |
| Xylenes (o-, m-, p- isomers) - (1330-20-7) | 4,299.00,<br>Rat -<br>Category: 5      | 1,548.00,<br>Rabbit -<br>Category: 4      | 20.00, Rat -<br>Category: 4           | No data available                         |
| Rosin - (8050-09-7)                        | 7,600.00,<br>Rat -<br>Category:<br>NA  | 2,500.00,<br>Rabbit -<br>Category: 5      | No data<br>available                  | No data available                         |
| Zinc oxide - (1314-13-2)                   | 5,000.00,<br>Rat -<br>Category: 5      | No data<br>available                      | No data<br>available                  | 2.50, Mouse -<br>Category: 4              |
| Glass, oxide, chemicals - (65997-17-3)     | No data<br>available                   | No data<br>available                      | No data<br>available                  | No data available                         |
| Iron oxide - (1309-37-1)                   | 10,000.00,<br>Rat -<br>Category:<br>NA | No data<br>available                      | No data<br>available                  | No data available                         |
| Benzene, ethyl- - (100-41-4)               | 3,500.00,<br>Rat -<br>Category: 5      | 15,433.00,<br>Rabbit -<br>Category:<br>NA | 17.20, Rat -<br>Category: 4           | No data available                         |
| Copper oxide - (1317-38-0)                 | 470.00, Rat<br>- Category:<br>4        | No data<br>available                      | No data<br>available                  | No data available                         |
| Barium sulfate - (7727-43-7)               | 3,000.00,<br>Mouse -<br>Category: 5    | No data<br>available                      | No data<br>available                  | No data available                         |

## Y3449F\_A9

|   |                             |                             |                   |                         |
|---|-----------------------------|-----------------------------|-------------------|-------------------------|
| Copper - (7440-50-8)  | 301.00, Rat - Category: 4   | 2,001.00, Rat - Category: 5 | No data available | 1.03, Rat - Category: 4 |
| BUTYL-N-CYCLOPROPYL-6-(METHYLTHIO)-1,3,5-TRIAZINE- (28159-98-0) | 2,000.00, Rat - Category: 4 | No data available           | No data available | No data available       |

| Item  | Category       | Hazard                               |
|---|----------------|--------------------------------------|
| Acute Toxicity (mouth)                                      | 4              | Harmful if swallowed.                |
| Acute Toxicity (skin)                                       | 5              | May be harmful in contact with skin. |
| Acute Toxicity (inhalation)                                 | Not Classified | Not Applicable                       |
| Skin corrosion/irritation                                   | 2              | Causes skin irritation.              |
| Eye damage/irritation                                       | 2              | Causes serious eye irritation.       |
| Sensitization (respiratory)                                 | Not Classified | Not Applicable                       |
| Sensitization (skin)  | 1              | May cause an allergic skin reaction. |
| Germ toxicity   | Not Classified | Not Applicable                       |
| Carcinogenicity   | Not Classified | Not Applicable                       |
| Reproductive Toxicity                                       | Not Classified | Not Applicable                       |
| Specific target organ systemic toxicity (single exposure)   | Not Classified | Not Applicable                       |
| Specific target organ systemic Toxicity (repeated exposure) | Not Classified | Not Applicable                       |
| Aspiration hazard   | Not Classified | Not Applicable                       |

## 12. Ecological information

## 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

## Aquatic Ecotoxicity

| Ingredient  | 96 hr LC50 fish, mg/l        | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l                                |
|---|------------------------------|----------------------------|--|
| Copper oxide (Cu <sub>2</sub> O) - (1317-39-1)                  | 0.075, Danio rerio           | 0.042, Daphnia similis     | 0.03 (96 hr), Pseudokirchneriella subcapitata    |
| Xylenes (o-, m-, p- isomers) - (1330-20-7)                      | 3.30, Oncorhynchus mykiss    | 8.50, Palaemonetes pugio   | 100.00 (72 hr), Chlorococcales                   |
| Rosin - (8050-09-7)   | 1.00, Danio rerio            | 10.00, Daphnia magna       | 100.00 (72 hr), Selenastrum capricornutum        |
| Zinc oxide - (1314-13-2)  | 1.10, Oncorhynchus mykiss    | 0.098, Daphnia magna       | 0.042 (72 hr), Pseudokirchneriella subcapitata   |
| Glass, oxide, chemicals - (65997-17-3)                          | Not Available                | Not Available              | Not Available                                    |
| Iron oxide - (1309-37-1)  | Not Available                | Not Available              | Not Available                                    |
| Benzene, ethyl- - (100-41-4)                                    | 4.20, Oncorhynchus mykiss    | 2.93, Daphnia magna        | 3.60 (96 hr), Pseudokirchneriella subcapitata    |
| Copper oxide - (1317-38-0)                                      | 25.40, Oncorhynchus mykiss   | 0.011, Daphnia magna       | 0.014 (72 hr), Pseudokirchneriella subcapitata   |
| Barium sulfate - (7727-43-7)                                    | 59,000.00, Poecilia sphenops | 32.00, Daphnia magna       | Not Available                                    |
| Copper - (7440-50-8)  | 0.0103, Pimephales promelas  | 0.0025, Daphnia magna      | 0.018 (72 hr), Pseudokirchneriella subcapitata   |
| BUTYL-N-CYCLOPROPYL-6-(METHYLTHIO)-1,3,5-TRIAZINE- (28159-98-0) | 0.84, Oncorhynchus mykiss    | 5.30, Daphnia magna        | 0.00147 (72 hr), Pseudokirchneriella subcapitata |

## 12.2. Persistence and degradability

No data available

## 12.3. Bioaccumulative potential

Not Measured

## 12.4. Mobility in soil

No data available

## 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

## 12.6. Other adverse effects

No data available

## 13. Disposal considerations

## 13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

## 14. Transport information

14.1. UN number UN 1263

14.2. UN proper shipping name PAINT

14.3. Transport hazard class(es)

## DOT (Domestic Surface Transportation)

DOT Proper Shipping Name PAINT

DOT Hazard Class 3 - Flammable

UN / NA Number UN 1263

DOT Packing Group III

CERCLA/DOT RQ 47 gal. / 881 lbs.

## IMO / IMDG (Ocean Transportation)

IMDG Proper Shipping Name PAINT

IMDG Hazard Class Sub Class 3 - Flammable Not applicable

IMDG Packing Group III

System Reference Code 181

14.4. Packing group III

14.5. Environmental hazards

IMDG Marine Pollutant: No ( Copper oxide (Cu<sub>2</sub>O) )

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

## 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B2 D2B

DOT Marine Pollutants (10%):  
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%)  
Copper

EPCRA 311/312 Chemicals and RQs (&gt;.1%) :

## Y3449F\_A9

Copper (5000 lb final RQ (no reporting of releases of this hazardous substance is required if the diame)

Benzene, ethyl- (1000 lb final RQ; 454 kg final RQ)

Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :

Copper

Benzene, ethyl-

Xylenes (o-, m-, p- isomers)

Mass RTK Substances (>1%) :

Barium sulfate

Copper

Benzene, ethyl-

Iron oxide

Xylenes (o-, m-, p- isomers)

Zinc oxide

Penn RTK Substances (>1%) :

Barium sulfate

Copper

Benzene, ethyl-

Iron oxide

Xylenes (o-, m-, p- isomers)

Zinc oxide

Penn Special Hazardous Substances (>.01%) :

(No Product Ingredients Listed)

RCRA Status:

(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

Barium sulfate

Copper

Benzene, ethyl-

Iron oxide

Xylenes (o-, m-, p- isomers)

Zinc oxide

N.J. Special Hazardous Substances (>.01%) :

2-Butoxyethanol

Benzene, ethyl-

Silica, cristobalite

Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%) :

Copper

Benzene, ethyl-

Xylenes (o-, m-, p- isomers)

Proposition 65 - Carcinogens (>0%):

Cadmium

Benzene, ethyl-

Lead

Quartz

Proposition 65 - Female Repro Toxins (>0%):

Lead

Benzene, methyl-

Proposition 65 - Male Repro Toxins (>0%):

Cadmium

Lead

Proposition 65 - Developmental Toxins (>0%):

Cadmium

Lead  
Benzene, methyl-

|                       |
|-----------------------|
| 16. Other information |
|-----------------------|

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.  
H226 Flammable liquid and vapor.  
H228 Flammable solid.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.

The following sections have changed since the previous revision.

SECTION 2: Hazards identification  
SECTION 3: Composition/information on ingredients  
SECTION 9: Physical and chemical properties  
SECTION 12: Ecological information  
SECTION 14: Transport information

End of Document