

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Perfection Pro YSC034 Matterhorn White

MSDS code : R62069

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Professional application of coatings and inks	
Uses advised against	Reason
For professional use only.	

1.3 Details of the supplier of the safety data sheet

Supplier : International Paint Ltd.
Stoneygate Lane
Felling
Gateshead
Tyne & Wear
NE10 0JY
United Kingdom
Tel: +44 (0)191 469 6111 Fax: +44 (0)191 438 3711
www.akzonobel.com/yacht

e-mail address of person responsible for this SDS : sds-cr@akzonobel.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : Not available.

Supplier

Telephone number : + 31 (0)71 308 6944

Hours of operation : 24 hours

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

STOT SE 3, H336

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

SECTION 2: Hazards identification

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : Flammable liquid and vapour.
 May cause drowsiness or dizziness.
 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
 No smoking.

Response : Not applicable.

Storage : Store in a well-ventilated place.

Disposal : Not applicable.

Hazardous ingredients : n-butyl acetate

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification Regulation (EC) No. 1272/2008 [CLP]	Type
n-butyl acetate	EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≥25 - <50	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	[1] [2]
heptan-2-one	EC: 203-767-1 CAS: 110-43-0	≥5 - <10	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H332	[1] [2]
Solvent naphtha (petroleum), light arom.	EC: 265-199-0 CAS: 64742-95-6 Index: 649-356-00-4	≥2 - <3	Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1]
2-methoxy-1-methylethyl acetate	EC: 203-603-9 CAS: 108-65-6	≥1 - <3	Flam. Liq. 3, H226	[2]

Date of issue/Date of revision : 10/24/2016. Version : 1

Date of previous issue : 10/14/2016. 2/14

SECTION 3: Composition/information on ingredients

1,2,4-trimethylbenzene	Index: 607-195-00-7 EC: 202-436-9 CAS: 95-63-6 Index: 601-043-00-3	≥1 - <3	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above.	[1] [2]
------------------------	---	---------	--	---------

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from

SECTION 4: First aid measures

short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO₂, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

- : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

- 7.1 Precautions for safe handling** :
- Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.
 - In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
 - Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.
 - Operators should wear antistatic footwear and clothing and floors should be of the conducting type.
 - Keep away from heat, sparks and flame. No sparking tools should be used.
 - Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.
 - Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.
 - Put on appropriate personal protective equipment (see Section 8).
 - Never use pressure to empty. Container is not a pressure vessel.
 - Always keep in containers made from the same material as the original one.
 - Comply with the health and safety at work laws.
 - Do not allow to enter drains or watercourses.
- Information on fire and explosion protection**
- Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Seveso II Directive - Reporting thresholds (in tonnes)

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c: Flammable liquids 2 and 3 not falling under P5a or P5b	5000	50000
C6: Flammable (R10)	5000	50000

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
n-butyl acetate	EH40/2005 WELs (United Kingdom (UK), 12/2011). STEL: 966 mg/m ³ 15 minutes. STEL: 200 ppm 15 minutes. TWA: 724 mg/m ³ 8 hours. TWA: 150 ppm 8 hours.
heptan-2-one	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin. STEL: 475 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 237 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.
2-methoxy-1-methylethyl acetate	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin. STEL: 548 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 274 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.
1,2,4-trimethylbenzene	EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 125 mg/m ³ 8 hours. TWA: 25 ppm 8 hours.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Individual protection measures

SECTION 8: Exposure controls/personal protection

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Use safety eyewear designed to protect against splash of liquids.

Skin protection

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Gloves : For prolonged or repeated handling, use the following type of gloves:

May be used: nitrile rubber, neoprene, butyl rubber

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Recommended mask :



P1A1

Environmental exposure controls : Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid.
Colour	: Product Specific Information
Odour	: Characteristic.
Odour threshold	: Not available.
pH	: Acidic.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: 126°C
Flash point	: Closed cup: 27°C
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Upper/lower flammability or explosive limits	: Greatest known range: Lower: 1.4% Upper: 7.6% (n-butyl acetate)
Vapour pressure	: Not available.
Vapour density	: Highest known value: 4.6 (Air = 1) (2-methoxy-1-methylethyl acetate). Weighted average: 4.04 (Air = 1)
Relative density	: 1.03
Solubility(ies)	: Not available.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (room temperature): 2.25 cm ² /s
Explosive properties	: Not available.
Oxidising properties	: Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-butyl acetate	LC50 Inhalation Vapour	Rat	390 ppm	4 hours
	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	10768 mg/kg	-
heptan-2-one	LD50 Oral	Rat	1600 mg/kg	-
	LD50 Oral	Rat	8400 mg/kg	-
Solvent naphtha (petroleum), light arom.	LD50 Oral	Rat	8400 mg/kg	-
	LD50 Oral	Rat	8400 mg/kg	-
2-methoxy-1-methylethyl acetate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	8532 mg/kg	-
1,2,4-trimethylbenzene	LD50 Oral	Rat	8532 mg/kg	-
	LD50 Oral	Rat	5 g/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Route	ATE value
Oral	27700.9 mg/kg
Inhalation (vapours)	160.2 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
n-butyl acetate	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
heptan-2-one	Skin - Mild irritant	Rabbit	-	24 hours 14 milligrams	-
		Rabbit	-	24 hours 100 microliters	-
Solvent naphtha (petroleum), light arom.	Eyes - Mild irritant	Rabbit	-	24 hours 100 microliters	-

Conclusion/Summary : Not available.

Sensitisation

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

SECTION 11: Toxicological information

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
n-butyl acetate 1,2,4-trimethylbenzene	Category 3 Category 3	Not applicable. Not applicable.	Narcotic effects Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name	Result
Solvent naphtha (petroleum), light arom.	ASPIRATION HAZARD - Category 1

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.
 Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
n-butyl acetate	Acute LC50 32000 µg/l Marine water	Crustaceans - Artemia salina - Nauplii	48 hours
heptan-2-one	Acute LC50 62000 µg/l Acute LC50 131000 to 137000 µg/l Fresh water	Fish - Danio rerio Fish - Pimephales promelas	96 hours 96 hours
1,2,4-trimethylbenzene	Acute LC50 4910 µg/l Marine water Acute LC50 22.4 mg/l Fresh water	Crustaceans - Elasmopus pecteniscrus - Adult Fish - Tilapia zillii	48 hours 96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
n-butyl acetate	2.3	-	low
heptan-2-one	2.26	-	low
Solvent naphtha (petroleum), light arom.	-	10 to 2500	high
2-methoxy-1-methylethyl acetate	1.2	-	low
1,2,4-trimethylbenzene	3.63	243	low

SECTION 12: Ecological information

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

Disposal considerations : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Type of packaging	European waste catalogue (EWC)
CEPE Paint Guidelines	15 01 10* packaging containing residues of or contaminated by hazardous substances

SECTION 13: Disposal considerations

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
UN number	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	3 	3 	3 
Packing group	III	III	III
Environmental hazards	No.	No.	No.
Additional information	Special provisions 640 (E) Tunnel code (D/E)	F-E, _S-E_ -	-

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

SECTION 15: Regulatory information

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

VOC for Ready-for-Use Mixture : Not applicable.

Seveso II Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

P5c: Flammable liquids 2 and 3 not falling under P5a or P5b

C6: Flammable (R10)

National regulations

Industrial use : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Inform Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

CEPE code : 1

Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

SECTION 16: Other information

Classification	Justification																						
Flam. Liq. 3, H226 STOT SE 3, H336 Aquatic Chronic 3, H412	On basis of test data Calculation method Calculation method																						
Full text of abbreviated H statements :	<table border="1"> <tr> <td>H226</td> <td>Flammable liquid and vapour.</td> </tr> <tr> <td>H302 (oral)</td> <td>Harmful if swallowed.</td> </tr> <tr> <td>H304</td> <td>May be fatal if swallowed and enters airways.</td> </tr> <tr> <td>H315</td> <td>Causes skin irritation.</td> </tr> <tr> <td>H319</td> <td>Causes serious eye irritation.</td> </tr> <tr> <td>H332 (inhalation)</td> <td>Harmful if inhaled.</td> </tr> <tr> <td>H335</td> <td>May cause respiratory irritation.</td> </tr> <tr> <td>H336</td> <td>May cause drowsiness or dizziness.</td> </tr> <tr> <td>H411</td> <td>Toxic to aquatic life with long lasting effects.</td> </tr> <tr> <td>H412</td> <td>Harmful to aquatic life with long lasting effects.</td> </tr> </table>	H226	Flammable liquid and vapour.	H302 (oral)	Harmful if swallowed.	H304	May be fatal if swallowed and enters airways.	H315	Causes skin irritation.	H319	Causes serious eye irritation.	H332 (inhalation)	Harmful if inhaled.	H335	May cause respiratory irritation.	H336	May cause drowsiness or dizziness.	H411	Toxic to aquatic life with long lasting effects.	H412	Harmful to aquatic life with long lasting effects.		
H226	Flammable liquid and vapour.																						
H302 (oral)	Harmful if swallowed.																						
H304	May be fatal if swallowed and enters airways.																						
H315	Causes skin irritation.																						
H319	Causes serious eye irritation.																						
H332 (inhalation)	Harmful if inhaled.																						
H335	May cause respiratory irritation.																						
H336	May cause drowsiness or dizziness.																						
H411	Toxic to aquatic life with long lasting effects.																						
H412	Harmful to aquatic life with long lasting effects.																						
Full text of classifications [CLP/GHS] :	<table border="1"> <tr> <td>Acute Tox. 4, H302</td> <td>ACUTE TOXICITY (oral) - Category 4</td> </tr> <tr> <td>Acute Tox. 4, H332</td> <td>ACUTE TOXICITY (inhalation) - Category 4</td> </tr> <tr> <td>Aquatic Chronic 2, H411</td> <td>LONG-TERM AQUATIC HAZARD - Category 2</td> </tr> <tr> <td>Aquatic Chronic 3, H412</td> <td>LONG-TERM AQUATIC HAZARD - Category 3</td> </tr> <tr> <td>Asp. Tox. 1, H304</td> <td>ASPIRATION HAZARD - Category 1</td> </tr> <tr> <td>EUH066</td> <td>Repeated exposure may cause skin dryness or cracking.</td> </tr> <tr> <td>Eye Irrit. 2, H319</td> <td>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2</td> </tr> <tr> <td>Flam. Liq. 3, H226</td> <td>FLAMMABLE LIQUIDS - Category 3</td> </tr> <tr> <td>Skin Irrit. 2, H315</td> <td>SKIN CORROSION/IRRITATION - Category 2</td> </tr> <tr> <td>STOT SE 3, H335</td> <td>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3</td> </tr> <tr> <td>STOT SE 3, H336</td> <td>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3</td> </tr> </table>	Acute Tox. 4, H302	ACUTE TOXICITY (oral) - Category 4	Acute Tox. 4, H332	ACUTE TOXICITY (inhalation) - Category 4	Aquatic Chronic 2, H411	LONG-TERM AQUATIC HAZARD - Category 2	Aquatic Chronic 3, H412	LONG-TERM AQUATIC HAZARD - Category 3	Asp. Tox. 1, H304	ASPIRATION HAZARD - Category 1	EUH066	Repeated exposure may cause skin dryness or cracking.	Eye Irrit. 2, H319	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2	Flam. Liq. 3, H226	FLAMMABLE LIQUIDS - Category 3	Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION - Category 2	STOT SE 3, H335	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	STOT SE 3, H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Acute Tox. 4, H302	ACUTE TOXICITY (oral) - Category 4																						
Acute Tox. 4, H332	ACUTE TOXICITY (inhalation) - Category 4																						
Aquatic Chronic 2, H411	LONG-TERM AQUATIC HAZARD - Category 2																						
Aquatic Chronic 3, H412	LONG-TERM AQUATIC HAZARD - Category 3																						
Asp. Tox. 1, H304	ASPIRATION HAZARD - Category 1																						
EUH066	Repeated exposure may cause skin dryness or cracking.																						
Eye Irrit. 2, H319	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2																						
Flam. Liq. 3, H226	FLAMMABLE LIQUIDS - Category 3																						
Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION - Category 2																						
STOT SE 3, H335	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3																						
STOT SE 3, H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3																						

Date of printing : 10/24/2016.

Date of issue/ Date of revision : 10/24/2016.

Date of previous issue : 10/14/2016.

Version : 1

Notice to reader**FOR PROFESSIONAL USE ONLY**

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Head Office

International Paint Ltd., Stonegate Ln, Gateshead NE10 OJY, United Kingdom. www.akzonobel.com/yacht

Date of issue/Date of revision : 10/24/2016. Version : 1

Date of previous issue : 10/14/2016. 14/14