

TECHNICAL DATA



Acrylic Wood Primer

Code 849 **5 litres**
Code 849c **20 litres**
Code 8491 **1000 litres**

DESCRIPTION

A water-borne, air-drying Acrylic Wood Primer. Manufactured from quality pigments and a special acrylic resin.

USES

Suitable for use on bare timber and masonry surfaces for both interior and exterior.

RECOMMENDED USES

Interior and exterior.

TYPE OF SUBSTRATE

Wood and masonry.

COLOUR RANGE

White.

FINISH

N/A

COVERAGE

Approximately 13 square metres per litre, depending on the nature and porosity of the surface being painted.

DRYING TIME

Touch dry in 30 minutes. Recoatable after 1-2 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position.
PROTECT FROM FROST.

THINNER

Clean water.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking materials. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

APPLICATION INSTRUCTIONS

Stir well. Easy to apply by brush or roller. Do not overspread. Also suitable for application by spray. Do not apply in temperatures below 5°C or externally when rain is imminent. When used externally the Primer must be kept dry before overcoating with a suitable external paint finish.

CLEANING

Remove as much product as possible from application equipment before washing. Replace lid firmly. Wash equipment immediately after use with warm soapy water. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

All products supplied by Biokil Crown Ltd are of high quality. The Company however cannot govern the conditions of usage and application of its products and any warrant written or implied covers materials only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss or injury or patent infringement arising from its use.



TECHNICAL DATA



PRECAUTIONS

PAINT PRODUCT

Ensure good ventilation during application and drying.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.

When spraying do not breathe spray, wear suitable respiratory protective equipment.

Keep out of reach of children.

HEALTH & SAFETY

Material Safety Data Sheet available on request.

VOC CONTENT

LOW VOC CONTENT 0.3-7.99%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.