



All Weather Sealant

A Universal Co-Polymer Sealant that can be used for a wide range of sealing and weatherproofing applications around the home and in industry. Can be applied in wet weather.

USES: Provides a superior adhesion to most surfaces such as glass, glazed surfaces, aluminium, lead and zinc. Can be used in building, glazing, roofing and ductwork applications and for emergency repairs in wet weather. Over paintable with most paints and stains.

COLOURS: Brown, White, Black, Clear, Grey

PACKAGING: 310ml cartridge packed 1 x 12

PREPARATION

All surfaces should be clean and dust free.

APPLICATION

Gun sealant firmly into joint ensuring no air is trapped behind. If required place masking tape along joint edges, removing within 5 minutes of application.

FINISHING

Always tool down using a spatula or stick wetted with soapy water within 5 minutes of application. Tack free in approximately 10 minutes. It is the user's responsibility to dispose of all packaging correctly.

HEALTH AND SAFETY

CAUTION: Highly Flammable
Do not smoke during use
Keep away from sources of ignition
Do not empty into drains
Keep out of reach of children

IRRITANT: Use in well ventilated areas
Do not take internally
Wear suitable gloves

LIMITATIONS

Do not use in joints subject to movement in excess of 15%. Do not use with aquaria. On surfaces containing bitumen or asphalt, discolouration can occur. It is users responsibility to determine suitability.

LIABILITY

The information given is the result of our tests and experience and is believed to be accurate and reliable. However, as Siroflex Limited cannot know all the uses its products may be put to, and as application methods are out of our control it is the users responsibility to determine suitability of use.

All products supplied by Biokil Crown Ltd are of high quality. The Company however cannot govern the conditions of usage and application of its products and any warrant written or implied covers materials only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss or injury or patent infringement arising from its use.



TECHNICAL DATA



TECHNICAL DATA	SX ALL WEATHER SEALANT
Movement accommodation	15% for joints up to 12mm
Shrinkage	Approx. 20%
Skimming Time	5 minutes
Cure Time	Approx. 0,5-1 mm per 24 hours at 23° C and 50% R.H. through evaporation of the solvent
Hardness Shore A	Acc. To ISO 828-23
Temperature Resistance	-20°C to +70°C
Modulus	Acc. to ISO 37 - 0,4 Mpa
Elongation	Acc. to ISO 37 - >400%
Specific Gravity	0.96
Paintability	With any home paint
Maintenance	With same material
Application Temperature	5°C to 40°C
Cleaning	with M.E.K
Shelf Life	12 months
Storage	Store in cool dry conditions
Minimum Joint Width	4 mm
Maximum Joint Width	10mm
Minimum Joint Depth	6mm

QUANTITY ESTIMATOR

Width x depth of joint x length (in linear metres) of joint, divide this by the volume of tube in ml= number of cartridges required.