



Anti-Mould Emulsion

Code 300 for 5 litres White
Code 303 for 5 litres Magnolia
Code 301 for 2.5 litres White
Code 304 for 2.5 litres Magnolia

USE

To protect against unsightly and unhygienic black mould. Can be used as a primer and undercoat for BIODIL CROWN Acrylic Eggshell or Gloss.

PROPERTIES

Guaranteed for FIVE YEARS
Prevents the recurrence of Black Mould
Quick drying with no overpainting problems
Compatible with all known paint finishes
Approved under HSE Control of Pesticides 1986 Regulations as a surface biocide treatment against mould growth
Easy to use and cost effective

DESCRIPTION

An excellent, premium quality, low odour antimould coating guaranteed to protect against unsightly and unhygienic black mould even when there is persistent condensation. The unsurpassed performance is achieved by combining modern paint technology with highly advanced, proven biocides. The antimould biocide is combined throughout the paint film, which is formulated to impart toughness, elasticity, water resistance and durability to the finish.

Ideal for walls and ceilings in private and social housing, and a wide range of public and commercial buildings. It is fully washable and resistant to the effects of condensation when the coating is fully dried out.

BIODIL CROWN Anti-mould Emulsion will help compliance with Section 82 (Statutory Nuisance), Chapter 43 of the Environmental Protection Act 1990, either used alone or part of various strategies to prevent condensation and mould growth in both private and public tenanted accommodation.

METHOD

Preparation

Remove loose material such as old paint, grease, dirt, mould or defective wallpaper. BIODIL CROWN Mould Wash can be used for "wetting in" purposes when removing wallpaper.

Make good any defects in the surface and rub down to a smooth finish.

Wash and clean all surfaces (walls, ceilings, window frames and joinery) using BIODIL CROWN Mould Wash. If necessary clean badly affected areas a second time.

Allow to dry thoroughly.

If necessary, apply an appropriate primer or sealer to new, unprimed or porous plaster and wooden surfaces or bare metal.

For new or porous plaster surfaces use BIODIL CROWN Anti-Mould Emulsion thinned up to 10% with clean tap water as normal good practice. Allow to dry thoroughly.

After priming metal surfaces should be painted with two coats BIODIL CROWN Anti-Mould Emulsion.

Application

Apply BIODIL CROWN Anti-Mould Emulsion using brush or roller.

STIR THOROUGHLY BEFORE USE.

Apply two coats BIODIL CROWN Antimould Emulsion allowing sufficient drying time between coats.

Clean equipment with clean tap water before the paint dries.

N.B.

If an unfinished, textured wallpaper (blown vinyl, woodchip) or similar is to be used then it should be hung after the BIODIL CROWN Mould Wash has fully dried. The wallpaper should be coated with BIODIL CROWN Antimould Emulsion as above.

DRYING TIME

Touch dry in 1 hour and recoatable after 2-4 hours dependent on conditions.

COVERAGE

10-12 m² per litre but an extra allowance should be made for rough or porous surfaces.

THINNING

Use clean tap water but do not exceed 10% by volume.

COLOURS

Brilliant White, Magnolia. Can be tinted with proprietary emulsion tinters.

All products supplied by Biokil Crown Ltd are of high quality. The Company however cannot govern the conditions of usage and application of its products and any warrant written or implied covers materials only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss or injury or patent infringement arising from its use.



TECHNICAL DATA



PACKAGING

1 2.5 and 5.0 litres in HPDE containers.

STORAGE

Store above 5 °C in dry conditions. Keep the container tightly sealed and away from children.

SAFETY

In use the product is very similar to conventional high quality emulsion paint; Refer to the Material Safety Data Sheet and the product label.

©HG 10/03