

TECHNICAL DATA



Heavy Duty Floor Paint

5 litre Red 926

5 litre Dark Grey 927

5 litre Light Grey 927L

20 litre RED 92620

20 litre Dark Grey 92720

20 litre Light Grey 927L20

DESCRIPTION

An air-drying solvent-based polyurethane semi-gloss finish based on a durable alkyd resin.

USES

Suitable for use on concrete and wooden floors in garages, factories and workshops. It can also be used on some asphalt floors, but a test application should be made to a small area to ensure that the asphalt is not softened or otherwise affected, and that the paint dries and hardens satisfactorily.

RECOMMENDED USES

Interior, walkways, garage floors.

TYPE OF SUBSTRATE

Concrete, and wooden floors. Also suitable for use on some asphalt floors. For further advice on other substrates contact our Technical Department.

COLOUR RANGE

Red, Dark Grey and Light Grey

FINISH

Mid Sheen.

COVERAGE

Approximately 12 square metres per litre, depending on the nature and porosity of the surface being painted. If 2 coats are required then first coat should be diluted with up to 20% white spirit to assist drying times.

DRYING TIME

Touch dry in 3 hours in normal dry conditions, can take much longer in cold, wet conditions. Generally, recoatable after 16-24 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position.
STORE AWAY FROM HEAT AND FLAME.

THINNER

White Spirit.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking materials. If the surface requires cleaning - this can be done by using a heavy duty degreasing agent for removing oil, grease and dirt from concrete floors. New concrete floors should preferably be allowed to mature for several months before painting. Concrete surfaces should also be free of dust, grit, cement fines and laitance. Very dense, smooth concrete surfaces (such as power floated concrete) normally require to be acid etched before painting in order to promote

All products supplied by Biokil Crown Ltd are of high quality. The Company however cannot govern the conditions of usage and application of its products and any warrant written or implied covers materials only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss or injury or patent infringement arising from its use.



TECHNICAL DATA



satisfactory adhesion. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Department.

APPLICATION INSTRUCTIONS

Stir well before use. Apply two coats, allowing overnight drying between coats under normal drying conditions. Where necessary, to ease application, the first coat should be thinned with up to 20% by volume of White Spirit.

CLEANING

Remove as much product as possible from application equipment before washing. Replace lid firmly. Wash equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

PAINT PRODUCT

FLAMMABLE

Contains Cobalt Carboxylate and Ethyl Methyl Ketoxime.

May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

Keep away from sources of ignition - No Smoking.

Ensure maximum ventilation during application and drying.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner - DO NOT USE SOLVENT OR THINNERS.

When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air fed respiratory protective equipment.

If swallowed, seek medical advice immediately and show the container or label.

Keep out of reach of children.

HEALTH & SAFETY

Material Safety Data Sheet available on request.

VOC CONTENT

HIGH VOC CONTENT 25-50%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.