

TECHNICAL DATA



Colourwood x AQ Woodstain

Colour Code	Mahogany	Pine	White	Red Cedar	Teak	Walnut	Black	Green
	780	781	782	783	784	785	786	787

A high performance translucent water-based woodstain. Based on exterior durable resin systems and weather resistant pigments that enhance the natural texture of the timber. Quick drying, produces a satin water repellent tack free microporous finish. Non-toxic, very low VOC content, flexible to prevent cracking, blistering etc. Contains a fungicide for lasting protection.

Uses:

All types of soft and hardwood to give a superb decorative wood finish which is tough, durable, flexible and water resistant.

Colour:

Mahogany, Pine, White, Red Cedar, Teak, Walnut, Black

Application:

Conventional or Airless Spray, brush or Dip application.

Recommended film thickness:

Dry film 25-75 microns.

Volume Solids:

Approx. 40%

Coverage:

12 sq. metres per litre

V.O.C. Level:

Below 100 grams per litre.

Drying Time:

30 mins at ambient temperature with good air flow.

Cure:

Allow 24 hours for full cure.

Recoat Time:

When Touch Dry.

Thinners:

Water

Flash Point:

Non-flammable.

Gloss:

Gloss to satin.

Surface Preparation:

Surface must be clean and completely free from contaminants.

Storage:

Store between 5° C and 30°c. Maximum storage period is 6 months in original containers.

Package:

5 litres

DATA SHEETS

All products supplied by Biokil Crown Ltd are of high quality. The Company however cannot govern the conditions of usage and application of its products and any warrant written or implied covers materials only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss or injury or patent infringement arising from its use.

