



Fire Retardant Expanding Foam

Code 923 700ml can Hand Held
Code 924 700ml can Gun Grade

Product description

Zwaluw DBS 9802-PUR is a one component fire retardant isolation and construction foam developed to make a fire retardant seal between stony construction parts.

The foam does cure in response to the humidity in the air and in the building materials.

Applications

joints between separation walls, ceiling and floors.

Limitations

Not recommended for locations subject to continuous water immersion and not for filling secluded areas or joints wider than 4 cm. Wider joints and joints deeper than 5 cm are to be filled in multiple layers. Waiting time between applications 15-30 minutes. Before each application lightly spray with water.

For outside use the foam surface has to be protected from UV-light. Cured foam can only be removed in a mechanical way.

Surface preparation and finishing
Surfaces must be clean and free of grease. Surfaces to be made slightly damp with a flower spray. Shake aerosol very well before use. Protect eyes and wear gloves and working clothes.

Tapestry, floor-covering and furniture to be covered with paper or plastic foil. Fresh foam can be removed directly with Purfoam cleaner, thinner or acetone.

After curing the surplus of the foam can be removed with a knife or spatula and the foam surface can be worked off.

Colour

Light red.

Packaging

700 ml aluminium aerosols with plastic tube.
700 ml aluminium aerosols with connection for NBS-guns.

Shelf Life

12 Months.

Safety

Safety Data Sheets are available upon request.

All products supplied by Biokil Crown Ltd are of high quality. The Company however cannot govern the conditions of usage and application of its products and any warrant written or implied covers materials only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss or injury or patent infringement arising from its use.

