



Zwaluw Hybrifix Super 7

Code 827 (White)

Code 939 (Black)

Code 828 (Brown)

Product description

Zwaluw Hybrifix Super 7 is a, high quality, strong one component adhesive/sealant based on MS polymer. The product is odourless, neutral and free of isocyanates.

After application the Zwaluw Hybrifix Super 7 cures with atmospheric moisture to form a durable rubber tough rubber.

Applications

1. Glueing of panels, skirting boards, windowsills, stripes, thresholds, mirrors and isolating materials in the building industry.

- Topsealing in glazing systems.
- Connecting joints in buildings.
- For kitchens and bathrooms.
- In coach-work and metal connecting joints.
- Sealing and glueing in shipbuilding industry.
- Universal filler for cracks and uneven surfaces.

In general Zwaluw Hybrifix Super 7 may be used, without primer, to seal assemblies of glass, glazed surfaces, porcelain, coated metal, epoxy and polyester panels, polystyrene, uPVC, stainless steel, anodised aluminium and finished wood. For porous surfaces like concrete we recommend to use a primer.

Limitations

Among others not recommended for application on PE, PP, Teflon and bituminous surfaces, underwater applications and for expansion joints.

Not paintable with alkyd resin paint.

Yellowing can occur in the dark.

Surface preparation and finishing

Surfaces must be clean, dry and sound. If necessary use a primer. See Primer Selection Guide and TB 02-95. Adhesion tests prior to the application are recommended. Finish joints with Zwaluw Finisher. See TB 03-95. Apply as an adhesive in a "ventilating" way in vertical stripes with 30 cm distance in between.

The use of two sided adhesive tape, 3 mm thick is recommended to support the adhesion during the first 24 hours and to make sure that the thickness of the adhesive is right.

Available colours

white, brown and black.

Packaging

Cartridges of 290 ml.

Shelf Life

9 Months.

Safety

Safety Data Sheets are available upon request.

All products supplied by Biokil Crown Ltd are of high quality. The Company however cannot govern the conditions of usage and application of its products and any warrant written or implied covers materials only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss or injury or patent infringement arising from its use.

