

TECHNICAL DATA



DATA SHEETS

Lead Sheet Sealant

Code 836 **Box**
Code 836T **Tube**

A high quality flexible mortar. Conforms to BS 5889 (A) and ISO11.600 F&G 25LM Glazing and Construction.

USES: Specifically formulated to point lead into brickwork. It cures by reaction with atmospheric moisture to give a flexible, waterproof joint. Provides good adhesion to lead and roofing substrates.

COLOURS: Grey

PACKAGING: 310ml cartridge packed 1 x 25

PREPARATION
Surfaces must be clean, dry and dust free.

APPLICATION
Gun sealant firmly into the joint to provide a solid fill.

FINISHING
Always tool down using a spatula or stick wetted with soapy water within 5 minutes of application. Curing time: tack free within 4-6 hours. It is the user's responsibility to dispose of all packaging correctly.

HEALTH AND SAFETY

CAUTION: Keep out of the reach of children. Do not take internally. Low hazardous product.

IRRITANT:
Avoid contact of uncured sealant with eyes. If contact occurs wash thoroughly with water. Avoid contact with skin, wear gloves. If irritation persists seek medical advice.

LIMITATIONS
For external use only. Do not use on areas subject to high abrasion. Not suitable for continuous water immersion.

QUANTITY ESTIMATOR
Width x depth of joint x length (in linear metres) of joint, divide this by the volume of tube in ml = number of cartridges required.

TECHNICAL DATA	LEAD SHEET SEALANT
Movement accommodation	+ or - 25%
Shrinkage	None
Skinning Time	5 minutes at 20°C
Cure Time	2mm/24 hours
Hardness Shore A	16
Temperature Resistance	-40°C to +100°C
Modulus	0.3 N/mm ²
Elongation	600%
Specific Gravity	1.03
Paintability	Not recommended
Maintenance	With same material
Application Temperature	+ 5°C to +30°C
Cleaning	Uncured material with White Spirit or MEK, Hands with water and soap
Shelf Life	9 Months
Storage	+5°C to +25°C
Minimum Joint Width	5mm
Maximum Joint Width	25mm
Minimum Joint Depth	5mm
Maximum Joint Depth	10mm

All products supplied by Biokil Crown Ltd are of high quality. The Company however cannot govern the conditions of usage and application of its products and any warrant written or implied covers materials only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss or injury or patent infringement arising from its use.

