



## Multi-Purpose Putty

A Multi Purpose Putty formulated for the glazing of wooden and metal window frames with single glass.

**COLOURS:** Natural & Brown

**PACKAGING:** 0.5 kg, packed 1 x 12      1 kg packed 1 x 12  
2 kg packed 1 x 6                      5 kg packed in singles  
10 kg packed in singles              25 kg packed in singles

### PREPARATION

Surfaces must be dry, clean, free from dust, rust, grease and oil. Un-primed wood and steel should be coated with one coat of a suitable primer. Before use mix well, especially if oil has separated from the mix. Never add any solvent, linseed oil or chalk to the product.

### APPLICATION

Apply the putty around the rebate and then carefully push in the glass, securing with glazing pins or clips. Now apply further putty around the edge of the glass. Knife off to give a smooth triangular fillet.

### FINISHING

The putty must be painted using an alkyd resin (gloss) paint as soon as the putty has formed a skin firm enough to accept the actions of overcoating. Apply the first coat usually within 7 - 21 days. The final coat should be applied within 28 days. It is the user's responsibility to dispose of all packaging correctly.

### HEALTH & SAFETY

**CAUTION:** Keep out of the reach of children  
Wash hands after use

### LIABILITY

The information given is the result of our tests and experience and is believed to be accurate and reliable. However as Siroflex Limited cannot know all the uses its products may be put to, and as application methods are out of our control it is the users responsibility to determine suitability of use.

All products supplied by Biokil Crown Ltd are of high quality. The Company however cannot govern the conditions of usage and application of its products and any warrant written or implied covers materials only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss or injury or patent infringement arising from its use.



# TECHNICAL DATA



<b>TECHNICAL DATA</b>	<b>SURESEAL MULTI PURPOSE LINSEED OIL PUTTY</b>
Character	Hardening
Specific Gravity	2.1
Skinning Time	Within a few days subject to temperature
Cure Time	Approx. 2 months subject to temperature
Shrinkage	None
Paintability	Yes
Maintenance	With the same material
Application Temperature	+5°C to +30°C
Shelf Life	6 months
Storage	Cool, dry conditions
Tool	Putty knife
Cleaning of tools	With white spirit
Cleaning of hands	With soap and water
Minimum Fillet Width	10mm
Maximum Fillet Width	25mm
Minimum Fillet Depth	8mm
Maximum Fillet Depth	15mm

## **QUANTITY ESTIMATOR**

1kg will glaze approximately 4 linear metres of glass.