

# TECHNICAL DATA



## Roof & Gutter Sealant

A rubberised sealant which provides a permanent water resistant and weatherproof seal. **Conforms to BS 6213: 1982 "Selection of Construction Sealants"**.

**USES:** Specially developed for repairing leaking gutters, down pipes and flashings. Can also be used for bedding roof sheets and felts.

**COLOURS:** Black

**PACKAGING:** 300ml cartridge packed 1 x 12

### PREPARATION

Surfaces must be clean, dry, free from frost, grease and loose material. Do not apply below +5°C. If required use masking tape along edges removing within 5 minutes of application.

### APPLICATION

Gun sealant firmly into joint to provide a solid fill, making sure no air is trapped behind.

### FINISHING

Always tool down within 5 minutes of application using a stick wetted with soapy water. Clean tools with white spirit. It is the user's responsibility to dispose of all packaging correctly.

### HEALTH & SAFETY

#### CAUTION

Contains white spirit. **Flash point +47°C until solvent is fully evaporated**  
Keep out of the reach of children

#### IRRITANT

Use only in well ventilated area  
Do not take internally  
Avoid contact with skin and eyes  
Wash hands immediately after use

#### LIMITATIONS

Not suitable for surfaces which can be affected by white spirit e.g. bitumen.

#### LIABILITY

The information given is the result of our tests and experience and is believed to be accurate and reliable. However, as Siroflex Limited cannot know all the uses its products may be put to, and as application methods are out of our control it is the users responsibility to determine suitability of use.

TECHNICAL DATA SHEET	S
Temperature Resistance	-20°C to +80°C
Application Temperature	+5°C to + 30°C
Shelf Life	12 months
UV Light Resistance	Good
Storage	Cool, dry conditions
Expected Life	Approx 15 years
Flash Point	+47°C

#### QUANTITY ESTIMATOR

Linear metres x cross section of joint in mm<sup>2</sup>, divided by pack volume in ml = number of cartridges required.

All products supplied by Biokil Crown Ltd are of high quality. The Company however cannot govern the conditions of usage and application of its products and any warrant written or implied covers materials only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss or injury or patent infringement arising from its use.

