

TECHNICAL DATA



Wood Stopper

Code 889 (Redwood)

Code 890 (Pine)

Code 891 (Oak)

Code 892 (Mahogany)

Woodstopper is an air dried stopper and woodfiller for small holes and grain filling. Based on a styrene acrylic emulsion Woodstopper offers many benefits over conventional stoppers :

- Water Based
- Non-Flammable
- Low Odour
- Non Hazardous
- Internal or External Use
- Ready for Use

APPLICATION

Prior to application the areas must be clean, dry, sound, any traces of oil or grease must be removed.

Apply Woodstopper to the area to be treated by knife, scraper or applicator leaving the filler slightly proud of the surface. Allow to dry and sand back smooth before overcoating.

On storage of Woodstopper, a small amount of liquid may form on the surface of the material, this can be readily remixed by stirring. If the lid is left off the container for a period of time a skin will form over the material. This skin should be removed and not mixed into the product.

TECHNICAL DATA

MATERIAL: WATER BASED ACRYLIC FILLER
MIXING
RATIO: AS SUPPLIED
DENSITY : NOMINAL 1.80 DEPENDENT ON COLOUR
DRYING: TOUCH DRY 15 MINUTES @ 20° C
HARD DRY 2 HOURS @ 20° C

SANDABLE: 30 MINUTES @ 20° C
OVERCOATABLE: 2 HOURS @ 20° C
APPLICATION
TEMP MIN: 10° C
COLOURS: 11 STANDARD COLOURS
PACK SIZE: HANDY PACK

WORKSHOP PACK

NB This material may change colour upon drying to a slightly darker shade. It may therefore be prudent to try a small sample area prior to full production.

All products supplied by Biokil Crown Ltd are of high quality. The Company however cannot govern the conditions of usage and application of its products and any warrant written or implied covers materials only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss or injury or patent infringement arising from its use.

