

Wireline Stem Section



The LiMAR® Wireline Stem Section, also known as Weight or Sinker Bar is designed to provide the necessary weight / mass to be able to deploy a wireline toolstring in the well, against well pressure.

Wireline Stem is also necessary for imparting sufficient upward and downward impact during jarring operations. Made from the highest quality material, LiMAR Wireline Stem is supplied in a range of diameters and lengths to suit customer requirements.



TOOL APPLICATIONS:

- Primarily designed to provide sufficient weight to overcome well pressure and impart necessary impact during jarring operations

DESIGN FEATURES & BENEFITS:

- Available in industry standard toolstring sizes
- Available in any length to suit customer requirements
- Connection options to suit customer requirements
- Selected components QPQ treated
- Hexagonal flats for safe make-up & break-out (in Sucker Rod option)

Assembly Part No.	Actual OD	Fish Neck	Connection	Length Options
1003-1250-XX-XXX-RX	1.250"	1.187"	Optional	2' / 3' / 4' / 5'
1003-1500-XX-XXX-RX	1.500"	1.375"	Optional	2' / 3' / 4' / 5'
1003-1750-XX-XXX-RX	1.750"	1.375"	Optional	2' / 3' / 4' / 5'
1003-1875-XX-XXX-RX	1.875"	1.750"	Optional	2' / 3' / 4' / 5'
1003-2125-XX-XXX-RX	2.125"	1.750"	Optional	2' / 3' / 4' / 5'
1003-2500-XX-XXX-RX	2.500"	2.313"	Optional	2' / 3' / 4' / 5'

XX - Denotes length
 XXX - Denotes connection type
 For additional sizes or further information please contact sales@limaroiltools.com