

Generators DIESEL

Single Phase or Three Phase, Large Tank

Generators Range

Applicable to material
and/or gasoline engine
(excluding Diesel engine)*

**3 YEARS
WARRANTY**

OUTPUT POWER
P_{max} 5.2 kW

ELECTRIC
START



OUTPUT POWER
P_{max} 5.2 kW

ELECTRIC
START

TRISTAR 6510 DTXL15

MASTER 6010 DXL15 YN DE

Very Long Autonomy

Standard Equipment

- ✓ 4-stroke Diesel engine
- ✓ Electric start + Battery
- ✓ Low oil pressure security
- ✓ Large tank
- ✓ Fuel gauge
- ✓ Sockets protected by thermal circuit breaker
- ✓ Brushless alternator, 2 poles (MASTER)
- ✓ Heavy duty steel frame

MASTER & TRISTAR - DIESEL

You need a generator with an industrial Diesel engine, this range offers you all the comfort of a construction site generator.



powered by
YANMAR

Wheelbarrow kit For moving your generator with 2 large wheels.



N/360 AXE
REF. 290000006

2000/14/EC

2000/14/EC

		Made in France	
		MASTER 6010 DXL15 YN DE	TRISTAR 6510 DTXL15 YN DE
Type		1 phase	3 phase / 1 phase
Voltage regulator		Capacitor	Compound
Maximum output	kW	5.2	5.2 / 3.7
Continuous operating power (COP)	kW	4.5	4.5 / —
Maximum output	kVA	—	6.5 / —
Maximum Amps	A	22.6	9.4 / 16
AC voltage	V	230	400 / 230
Frequency	Hz	50	50
Noise power level CEE (L _{WA})	dB(A)	103	103
Noise power level @ 7 m	dB(A)	78	78
Engine model		YANMAR L100V5	YANMAR L100V5
Maximum output	HP	9.3	9.3
Fuel type		Diesel ²	
Fuel tank capacity	L	15	15
Autonomy (¾ of the continuous output)		9 h 45	9 h 45
Single phase socket 10/16 A Schuko	⚡	1	1
EC Single phase socket 230 V / 32 A	⚡	1	—
EC Three phase socket 400 V / 16 A	⚡	—	1
Dimensions L x l x H	mm	875 x 535 x 635	875 x 535 x 635
Packaging dimensions L x W x H	mm	895 x 555 x 655	895 x 555 x 655
Net Weight (Gross weight)	kg	95.5 (99.5)	120 (126)
Reference standard version (Std.)		2V0000054	2V0000049
Reference Std. version + DIFF		2V0000054.1	2V0000049.3
Reference Std. version + AVR		2V0000054.2	2V0000049.1
Reference Std. version + DIFF + AVR		2V0000054.3	2V0000049.2

Optional equipments

Wheelbarrow kit	N/360 AXE	N/360 AXE
DE: Electric start + Battery	standard	standard
AVR: Automatic voltage regulator	factory option	factory option
DIFF: Kit interdif *	factory option	factory option

* Kit interdif = Earth leakage circuit breaker 30 mA + Steel Ground Rod + box

2000/14/EC Equipment intended to be installed with all the proper rules, inside a building or reserved for use in a country not subject to Directive 2000/14/EC (excluding UE and affiliated countries).

¹ Diesel engines are warranted separately by the engine manufacturer conditions.

² Do not use domestic or heating oil.