

Model : JST37

4" Drainage pump - 230V



Operation

Liquid	Drainage
Capacity	1200 l/m (108 m3/h)
Delivery head	24m

Technical details

Delivery connection:	4" Female thread
Nett Weight:	42 kg
Gross Weight:	44 kg
Solid handling:	10mm diameter

Materials

Motorcasing:	RVS 316
Shaft seal:	SIC / CC
Impeller:	Cast Iron
Shaft:	RVS 304
Pump Casing	Cast Iron

Motor

Absorbed Power (P1):	5.0kW
Rated power (P2):	3.7W
Nominal Current:	16A
Protection class:	IP68
Power Cable	10m H07-RNF
Voltage / Phase / Hz:	230v / 3-Phase / 50Hz
Motor Protection:	Thermal

Additional information

Max. Submerged depth:	20m
Max. Liquid temp.:	40 °C
pH Liquid:	6 - 8
Solid handling:	10mm solids
Switch options:	Control panel

Contractor Drainage pump

Usage:

- Drainage
- Floodwater

Unique properties

The RS series of pumps are designed with a top outlet allowing the pumped liquid to cool the motor. Providing for a durable and reliable pump.

** Picture may differ from actual product

Due to the durable construction, the JS Pumps have a very long operational life and are easy to maintain.

Specifications are subject to change by the manufacturer.

Dimension:

H x W x L = 525 x 220 x 320mm

