






SPECIFICATION	MEASUREMENTS
Maximum Screen Size	65" - 115"
Maximum Weight Capacity	120Kg (265lb)
Maximum Extension From Wall	569mm (22 3/8")
Depth From Wall	84mm (3 5/16")
Packaging Dimensions	1170 x 380 x 200mm (46" x 14 15/16" x 7 7/8")
Shipping Weight	20Kg (44lb)
Maximum Rotation	115" Screen - 25°
Movement Type	Manual
Mounting Patterns Supported	VESA 1000, 800, 700, 600, 500, 400, 300, 200 W x 700, 600, 500, 400, 300, 200 H
Product Options / Features	Specific B&O and Loewe mounts / adapters, Custom RAL paint finishes, WB80
Package Contents	Mechanism
Marine Suitable	No




GENERAL DIMENSIONS







WALL PLATE DIMENSIONS







RECESS MOUNTING

When recess mounting a screen on the PS80 the gap around the edge can be as little as 5mm [0.2]. Ventilation would have to be provided by opening the top and maybe the bottom of the recess.

A larger gap of 50mm [2.0"] around the screen would enable extra ventilation and enough space for finger access to manoeuvre the screen if required.









MOUNTING DETAILS

The whole area of the wall plate needs to be well supported. Ideally solid plaster over brickwork.

If mounting to a stud work wall its important to have 2 vertical studs behind on both sides of the wall plate. See details A & B.







SHEET 6



MOUNTING DETAILS







SWIVEL ANGLE

A maximum angle of 25 $^{\circ}$ is achievable when mounting the Samsung 115" screen.

