

# Double Standard Magnet

## 10040/60

- Operating Voltage: 12 or 24Vdc
- Brushed aluminium
- Current draw: 500mA at 12Vdc  
250mA at 24Vdc (at temperature 20°C)
- Magnetic bond sensor monitor output remotely monitors the door lock or unlock status. (N.C. Output-Door opened; N.O. Output-door closed) (SPDT rated 3A at 12Vdc)
- Status LED lights
- Operating temperature: -10 to 55°C (14 to 131°F)
- Humidity: 0 to 95% non-condensing
- Lock's surface temperature: Current temperature ±20% (when power is on)
- Holding force: Up to 1200lbs x 2 (545kg x 2)
- Weight: 8.0kg (approx)



VARIATIONS	
10060	Dbl. Standard Magnet
10060DS	Dbl. Standard Magnet C/W Door Status
10040	Dbl. Standard Monitored Magnet
10040DS	Dbl. Standard Monitored Magnet C/W Door Status

DIMENSIONS	LENGTH	WIDTH	DEPTH
Magnet	532	68	40
Armature Plate	185	62	16

All dimensions in mm



**ICS Security Solutions Ltd - Your Security Solutions Partner**

Units 1-2 JBJ Business Park Northampton Road Blisworth Northampton NN7 3DW  
Telephone: 01604 858565 Facsimile: 01604 859545 Email: [orderline@icssecurity.co.uk](mailto:orderline@icssecurity.co.uk)

