



**CONSTRUCTION PRODUCTS REGULATION 2011
DECLARATION OF PERFORMANCE**

DoP Number:

VT10001 VT10004

1. Unique identification code of the product-type:

VT10001 VT10004

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

VT10001 VT10004

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For use on fire and smoke compartmentation doors, when fitted in accordance with the manufacturer's fitting instructions.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

ASEC VITAL
22 Parr Street, Clinton House , London, UNITED KINGDOM N1 7GW , United Kingdom

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 12209: 2003 incorporating Corrigendum N° 1 Notified product certification body No. (Fill in the Notified Body number below) performed the determination of the product type on the basis of type testing (including sampling); initial inspection of the manufacturing plant and of the factory production control and continuous surveillance; assessment and evaluation of factory production control; and issued the certificate of constancy of performance of the product.

Enter Notified Body Number Here

BSI

8. European Technical Assessment:

N/A

9. Declared performance

Essential characteristic	Performance	Harmonised technical specification
Self closing		
5.4.2 Closing force	Grade 8, Up to 200 kg door mass, 15 N max. closing force	EN 12209: 2003 incorporating Corrigendum N° 1
5.1.2 Re-latching force of latch bolt	Deadlock – N/A	
Durability of self closing		
5.3.1 Durability of latch action	Deadlock – N/A	EN 12209:2003 incorporating Corrigendum N° 1
Ability to maintain the door in the closed position and not contribute to the spread of fire	Grade 1	
Dangerous Substances Annex ZA3		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



DIP GAI MINST AI

PRODUCT MANAGER

Date of issue: 20/03/2020

Aldridge Security Ltd, 22 Parr Street, Clinton House
London, UNITED KINGDOM N1 7GW
United Kingdom

This Declaration of Performance is issued on a standard template provided by the GAI for use in the door and hardware industries. There is no implied endorsement of the content, which is the responsibility of the issuing company.

The Guild of Architectural Ironmongers
BPF House, 6 Bath Place, Rivington Street, London, EC2A 3JE
Tel: +44 (0) 20 7033 2480 | Fax: +44 (0) 20 7033 2486

