



CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

DoP Number:

AS3101 AS3102

1. Unique identification code of the product-type:

AS3101 PANIC LATCH LH SE
AS3102 PANIC LATCH RH SE

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

AS3101 PANIC LATCH LH SE
AS3102 PANIC LATCH RH SE

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For use on escape route doors, when fixed in accordance with the manufacturer's fitting instructions

For use on fire and smoke compartmentation doors, when fixed in accordance with the manufacturer's fitting instructions

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

ASEC
ALDRIDGE SECURITY LTD, 32-34 EAGLE WHARF ROAD, LONDON N1 7EG, United Kingdom

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard.

EN 1125:2008. Notified product certification body No. 1121 performed the determination of the product type on the basis of type testing (including sampling); initial inspection of the manufacturing plant and of the factory production control and continuous surveillance; assessment and evaluation of factory production control; and issued the certificate of constancy of performance of

the product.

8. European Technical Assessment:

N/A

9. Declared performance

| Essential characteristic | Performance | Harmonised technical specification |
|---|--|------------------------------------|
| Clause 4.2.1 Ability to release (for doors on escape routes) | | EN 1125:2008 |
| Release function | Not exceeding 1 sec | |
| Panic exit device mounting | Pass | |
| Exposed edges and corners | Not exceeding 0.5 mm | |
| Double doorset | Pass | |
| Bar installation | Z not more than 150 mm from frame stop | |
| Bar length | At least 60% of max door width | |
| Bar projection | W not more than 100 mm; | |
| Bar end | Pass | |
| Operating bar face | V not less than 18 mm | |
| Test rod | Pass | |
| Door face gap | R not less than 25 mm | |
| Accessible gap | Pass | |
| Door free movement | Pass | |
| Top vertical bolt | Pass | |
| Keepers | Pass | |
| Floor keepers dimensions | H - not more than 15 mm M - not more than 45° P - not more than 3 mm | |
| Door mass and dimensions | Door mass up to 200 Kg door height up to 2520 mm, door width up to 1320 mm | |
| Outside access device | Pass | |
| Release forces | Not more than 80 N with the door unloaded Not more than 220 N with the door loaded with 1000 N | |
| Security requirement | Grade 2 | |

| Essential characteristic | Performance | Harmonised technical specification |
|--|---|------------------------------------|
| Clause 4.2.1 Durability of ability to release against aging and degradation (for doors on escape routes) | | EN 1125:2008 |
| Corrosion resistance | Grade 3: 96 hrs | |
| Temperature range | Operating forces at -10C° and + 60C° not more than 50% in excess of the operating forces at +20C° | |
| Covers for vertical rods | N/A | |
| Lubrication | Lubrication every 20 000 cycles | |
| Re-engagement force | Not greater than 50 N | |
| Durability | Grade 7: 200 000 cycles | |
| Abuse resistance - Horizontal bar | 1 000 N | |
| Abuse resistance - Vertical rod | N/A | |
| Final examination | Not more than 80 N with the door unloaded Not more than 220 N with the door loaded with 1 000 N | |
| Clause 4.2.1 Self closing ability C (for fire/smoke doors on escape routes) | | |
| Re-engagement force | Not more than 50 N | |
| Clause 4.2.1 Durability of self closing ability C against aging and degradation (for fire/smoke doors on escape routes) | | |
| Durability | Grade 7: 200 000 cycles | |
| Re-engagement force | Not more than 50 N | |
| Clause 4.2.1 Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes) | | |
| Suitability of panic exit devices for use on fire resisting doorsets or assemblies - Additional requirements | Grade B: Suitable for use on fire/smoke door assemblies | |
| Dangerous Substances Annex ZA3 | The materials in the product(s) do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations. | |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

MR CHRISTOPHER THORPE DIP GAI MINST AI

PRODUCT MANAGER



Date of issue: 19/06/2013

ALDRIDGE SECUIRTY LTD
32-34 EAGLE WHARF ROAD, LONDON N1 7EG
United Kingdom

This Declaration of Performance is issued on a standard template provided by the GAI for use in the door and hardware industries. There is no implied endorsement of the content, which is the responsibility of the issuing company.



The Guild of Architectural Ironmongers
BPF House, 6 Bath Place, Rivington Street, London, EC2A 3JE
Tel: +44 (0) 20 7033 2480 | Fax: +44 (0) 20 7033 2486