

# Optimus3 - 72mm Spec lockcases

2E25

Euro Profile Deadlocking Nightlatch



## Application:

- Modular lockcase range for doors hinged on the left or right
- European style casing with 72mm centres which are designed to suit DIN standard Euro profile cylinders
- Latch bolt withdrawn by the lever handle from either side
- Key operation from the outside of the door and single handle operation from the inside
- Latch bolt is automatically deadlocked against end pressure by the anti-thrust bolt
- Pierced to accept bolt through furniture and security roses
- Suitable for sprung and unsprung lever furniture up to a maximum of 0.97Kg

## Specification:

- Two piece forend for clean aesthetics
- Easily reversible latch bolt
- Available with radiused or square forend and strike
- Supplied with an adjustable formed strike
- **Positive 1° follower angle to help maintain the appearance of the door furniture over time by reducing lever droop**
- Cylinder to latch functionality
- Reference L2E25
- Case Size 90mm
- Backset 60mm
- Centres 72mm
- Case Steel, painted
- Forend Stainless steel
- Striking Plate Stainless steel
- Deadbolt Steel, hard chrome plated
- Latch Bolt Steel, hard chrome plated
- Follower 8mm
- Cylinder Type Euro profile (not supplied)

## Finish:

- SS - Stainless Steel



## Standards:

- Tested to BS EN 12209 : 2003  

3	X	8	1	0	G	1	B	B	2	0
---	---	---	---	---	---	---	---	---	---	---
- EN 1634-1 assessed for use on 60 minutes timber fire doors
- EC Certificate number
  - 1121-CPD-AG5007
- Assists in fulfilling duties required under the Equality Act. Satisfies recommendations of BS8300 and Approved Document M (ADM)
- 10 year guarantee



