



SAFETY DATA SHEET

PRITT STICK

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME	PRITT STICK
PRODUCT NO.	260810,260811,260812,261383,261385,261386,261387,261388,261395,261396,261397,261398,653567,653069,677308,678785,694053,695979
APPLICATION	Adhesive
SUPPLIER	Henkel Consumer Adhesives Road 5, Winsford Industrial Estate Winsford Cheshire CW7 3QY T: 01606 593933 F: 01606 863762 E: technical.services@henkel.co.uk

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
CAPROLACTAM -Eta	203-313-2	105-60-2	1-5%	Xn;R20/22 Xi;R36/37/38
HYDROGEN PEROXIDE SOLUTION ... %	231-765-0	7722-84-1	< 1%	O;R8 C;R34
SODIUM HYDROXIDE	215-185-5	1310-73-2	< 1%	C;R35

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Water based solid adhesive masse

3 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

4 FIRST-AID MEASURES

INHALATION

Not relevant.

INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort continues.

SKIN CONTACT

Wash skin with soap and water. Get medical attention if irritation persists after washing. Contact physician if irritation continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Non-hazardous substance. No specific clean-up procedure noted.

7 HANDLING AND STORAGE

PRITT STICK**USAGE PRECAUTIONS**

No specific usage precautions noted.

STORAGE PRECAUTIONS

Keep in original container. Store below 25°C.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
HYDROGEN PEROXIDE SOLUTION ... %	OES	1 ppm	1.4 mg/m3	2 ppm	2.8 mg/m3
CAPROLACTAM -Eta	OES		10 mg/m3		20 mg/m3
SODIUM HYDROXIDE	OES				2 mg/m3

INGREDIENT COMMENTS

OES = Occupational Exposure Standard. MEL = Maximum Exposure Limit.

ENGINEERING MEASURES

No particular ventilation requirements.

HAND PROTECTION

No specific hand protection noted, but gloves may still be advisable.

EYE PROTECTION

Not relevant.

OTHER PROTECTION

Not relevant.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Soft Opaque Solid		
COLOUR	White to White / off-white		
ODOUR	Characteristic Mild (or faint). Perfume scent		
SOLUBILITY	Soluble in water		
MELTING POINT (°C)	~ 50	RELATIVE DENSITY	~ 1.13 @ 20 °c
pH-VALUE, CONC. SOLUTION	~ 10		

10 STABILITY AND REACTIVITY**STABILITY**

Stable under normal temperature conditions. Avoid: Freezing.

CONDITIONS TO AVOID

Avoid heat.

HAZARDOUS DECOMPOSITION PRODUCTSFire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).**11 TOXICOLOGICAL INFORMATION****HEALTH WARNINGS**

No specific health warnings noted.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

ROAD TRANSPORT NOTES Not Classified

PRITT STICK

RAIL TRANSPORT NOTES Not Classified.
SEA TRANSPORT NOTES Not Classified.
AIR TRANSPORT NOTES Not Classified.

15 REGULATORY INFORMATION

RISK PHRASES
NC Not classified.

SAFETY PHRASES
NC Not classified.

STATUTORY INSTRUMENTS
Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE
Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES
Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16 OTHER INFORMATION

ISSUED BY
Technical Services Department, Winsford, Cheshire
REVISION DATE 09-11-2004

RISK PHRASES IN FULL
R20/22 Harmful by inhalation and if swallowed.
R34 Causes burns.
R35 Causes severe burns.
R36/37/38 Irritating to eyes, respiratory system and skin.
R8 Contact with combustible material may cause fire.

DISCLAIMER

Every effort has been made to ensure that this information is accurate and up to date. , Users are reminded that they should ensure that they have retained or internally circulated the most up to date copy as provided to the persons or work locations which require them. , No warranty is implied or given as to suitability for use for any activity which is not covered by either the technical data sheet or restrictions of use as above.