

## Laserliner 036.730E SmartCross-Laser GX Cross-Line Laser

**STOCK No.** 32158 **BRAND** Laserliner

**BARCODE** 4021563731503

**WARRANTY** 4 Years



### FEATURES

- Sustainable design: large proportion of the housing is made from recycled plastic
- Accurate horizontal and vertical alignment of objects
- Good visibility through green laser technology
- Easy alignment of slopes with manual tilt function
- Time-saving automatic alignment
- Integrated hand-held receiver mode for outdoor applications
- Visual signals indicate when the device is outside its self-levelling range
- Pendulum restraint for safe transport
- Supplied with battery

### DESCRIPTION

This cross-line laser projects a highly visible green laser cross for precise horizontal and vertical alignment of objects. It also offers a manual slope function for easy creation of gradients and a 1/4" thread for mounting on a tripod. The laser can also be used for outdoor applications and alignment work at long distances with the integrated hand-held receiver mode. The housing of the laser is made from a large proportion of recycled plastic and makes a valuable contribution to sustainability. Supplied with battery.

### CONTENTS

- 1 x Laserliner 036.730E SmartCross-Laser GX Cross-Line Laser
- 1 x Batteries

[Link to product - drapertools.com](https://www.drapertools.com)

## SPECIFICATIONS

|                               |                                                       |
|-------------------------------|-------------------------------------------------------|
| Horizontal/vertical levelling | Yes                                                   |
| Manual slope function         | Yes                                                   |
| Battery operation             | Yes                                                   |
| Hand receiver mode            | Yes                                                   |
| Self-Levelling Range          | ± 4°                                                  |
| Accuracy                      | ±0.3 mm/m                                             |
| Levelling                     | Automatic                                             |
| Visibility (Typical)*         | 40 m                                                  |
| Laser Wavelength              | 515 nm                                                |
| Laser Class                   | 2 / < 1 mW (EN 60825-1:2014/A11:2021 / EN 50689:2021) |
| Power Supply                  | 2 x 1.5V LR6 (AA)                                     |
| Operating Time                | approx. 6 hours                                       |
| Operating Condition           | -10°C ... 50°C                                        |
| Storage Conditions            | -20°C ... 70°C                                        |
| Dimensions (W x H x D)        | 84 mm x 76 mm x 62 mm                                 |
| Weight                        | (incl. Batteries)                                     |

## DOCUMENTS



Instruction Manual