




GIGALITHIUM ⚡ 12 V 🔋 800 CA



In option: Docking station



+++

4-cell lithium LiFePO4
100% safe

Lightweight

LCD screen

Microprocessor controlled

Protection against
over discharge

Protection against
over charge

Protection against
over temperature

Protection against
reverse polarity

Protection against
short circuit

Protection against
voltage error and overload

Override mode

Memory saver





LITHIUM JUMP STARTER

GIGALITHIUM ⚡ 12/24 V 🔌 2000/1000 CA



In option: Docking station



+++

4-cell lithium LiFePO4
100% safe

Lightweight

LCD screen

Microprocessor controlled

Protection against
over discharge

Protection against
over charge

Protection against
over temperature

Protection against
reverse polarity

Protection against
short circuit

Protection against
voltage error and overload

Override mode

Memory saver



LCD





GIGALITHIUM 12 V



GIGALITHIUM 12/24 V

TECHNICAL INFORMATION

MODEL	GIGALITHIUM 12 V	GIGALITHIUM 12/24 V
PART NUMBER	805600100	805600200
VOLTAGE (DC)	12 V	12/24 V
CRANKING AMPS (CA)	800	2000/1000
CABLE LENGTH	0,50 m	1,60 m
CABLE CROSS SECTION	10 mm ²	25 mm ²
AUTOMATIC CHARGER	1 A	4 A



PACKAGING INFORMATION

MODEL	GIGALITHIUM 12 V	GIGALITHIUM 12/24 V
NET WEIGHT	3 kg	6,25 kg
DIMENSIONS (L x W x h) mm	445 x 250 x 115	400 x 345 x 210

HOW TO CHOOSE

PART NUMBER	MODEL	VOLTAGE	12 V						24 V			
			<125*	150	175	250	300	500	100	250	500	1000
			HP* = CHECK YOUR ENGINE HP - LEGEND: ■ NORMAL ■■ INTENSIVE									
805600100	GIGALITHIUM	12 V	■■	■■	■	■						
805600200	GIGALITHIUM	12/24 V	■■	■■	■■	■	■		■■	■■		