#### SAFETY DATA SHEET

Version: 1

Product Name: Lithium-ion Rechargeable Battery Issue Date: 02-Feb-2018

# a Identification of the product and supplier.

Name of product:

Lithium-ion Rechargeable Battery For 20890, 21450, 82093, 82099

Details of the supplier of the Safety Data Sheet

Draper Tools Ltd Hursley Road Chandlers ford Eastleigh Hampshire SO53 1YF

Draper Helpline + 44 (0) 2380 494 344

## 2 Hazanos Identification

| Explosive risk   | This article does not belong to the explosion dangerous goods.      |  |
|------------------|---|--|
| Flammable rick   | This article does not belong to the flammable material.             |  |
| Oxidation risk   | This article does not belong to the oxidation of dangerous goods.   |  |
| Toxic risk       | This article does not belong t the toxic dangerous goods.           |  |
| Radioactive risk | This article doe not belong to the radiation of dangerous goods.    |  |
| Mordant risk     | This article does not belong to the corrosion of dangerous goods.   |  |
| Other risk       | This article is the Li-on Cell, watt hour rate respectively 4.81Wh; |  |
|                  | 5.55Wh; 7.4Wh; 8.14Wh.  |  |

# 3 Composition/information on Ingredient

| 危险成分 (化学名称)<br>Hazardous Ingredients<br>(Chemical Name) | 含量及含量百分比(%)<br>Concentration or concentration<br>ranges (%) | CAS编号<br>CAS Number     |
|---|---|-------------------------|
| 非丙烯/ Polypropylene;                                     | 0.3   | 9003-07-0               |
| 伙 Nickel (Ni)   | 15.5  | 7440-02-0               |
| 铁/ Iron   |   | 7439-89-6               |
| 铝/ Aluminium (AI)                                       | 3.88  | 7429-90-5               |
| 镍/ Nickel (Ni)  |   | 7440-02-0               |
| 鉄/ Iron   |   | 7439-89-6               |
| 聚丙烯/ Palypropylene;                                     | 1 .   | 9003-07-0               |
| 六氯磷酸锂/ Lithium hexafluorophosphate                      | 14.3  | 21324-40-3              |
| 碳酸甲乙酯/ Ethyl methyl carbonate                           |   | 623-53-0                |
| 碳酸二甲酯/ Dimethyl carbonate                               | ]   | 616-38-6                |
| 镍钴G酸锂/ LIMn1-x-yNixCoyO2                                | 28.27   | 182442-95-1             |
| 石器/ Graphite  | 17.8  | 7782-42-5               |
| 炭黑/ Carbon Black  | 1.2   | 1333-86-4               |
| 聚翛狐乙烯/ Polyvinylidene Fluoride (PVDF)                   | 1.75  | 24 <del>9</del> 37-79-9 |
| 铜/ Copper (Cu)  | 9.71  | 7440-50-8               |
| 铝/ Aluminium (Al)                                       | 6.22  | 7429-90-5               |
| 嫁/ Nickel (Ni)  | 0.97  | 7440-02-0               |
| 隔膜/ Diaphragm   | 0.1   |                         |

### 4 Firstlaid measures (急激槽施

Eve

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

Skin

Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.

Inhalation

Remove from exposure and move to fresh air immediately. Use oxygen if available.

Ingestion

Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.

### 5. Fire-fighting measures (消防措施)

Flash Point: N/A.

Auto-Ignition Temperature: N/A.

Extinguishing Media: Water, CO2.

Special Fire-Fighting Procedures

Self-contained breathing apparatus.

Unusual Fire and Explosion Hazards

Cell may vent when subjected to excessive heat-exposing battery contents.

**Hazardous Combustion Products** 

Carbon monoxide, carbon dioxide, lithium oxide fumes.

### 6. Accidental release measures (泄漏应急处理

Steps to be Taken in case Material is Released or Spilled

If the battery material is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. Wipe it up with a cloth, and dispose of it in a plastic bag and put into a steel can. The preferred response is to leave the area and allow the battery to cool and vapors to dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate.

Waste Disposal Method

Report No: 18PNS01159 01001

It is recommended to discharge the battery to the end, to use up the metal lithium inside the battery, and to bury the discharged battery in soil.

### 7. Handling and storage (操作处置和储存

The battery should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container. Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire.

Do not crush or puncture the battery, or immerse in liquids.

Precautions to be taken in handling and storing

Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.

Other Precautions

The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

### 8. Exposure controls/personal protection (会触控制/个人保护)

#### Respiratory Protection

In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores. Respiratory Protection is not necessary under conditions of normal use.

Ventilation

Not necessary under conditions of normal use.

Other Protective Clothing or Equipment

Not necessary under conditions of normal use.

Personal Protection is recommended for venting battery

Respiratory Protection, Protective Gloves, Protective Clothing and safety glass with side shields.

## 9. Physical and chemical properties (勿理和火坐传社)

Appearance: Cylindrical shape

Ref. No.: N/A

Odour: If leaking, smells of medical ether.

pH: Not applicable as supplied.

Flash Point: Not applicable unless individual components exposed.

Flammability: Not applicable unless individual components exposed.

Relative density: Not applicable unless individual components exposed.

Solubility (water): Not applicable unless individual components exposed.

Report No: 18PNS01159 01001

Solubility (other): Not applicable unless individual components exposed.

### 10. Stability and reactivity 稳定性和反应活性

Stability: Product is stable under conditions described in Section 7.

Conditions to avoid: Heat above 70°C or incinerate, Deform, Mutilate, Crush, Disassemble, Overcharge,

Short circuit. Expose over a long period to humid conditions.

Materials to avoid: Oxidising agents, alkalis, water.

Hazardous Decomposition Products: Toxic Fumes, and may form peroxides.

Hazardous Polymerization: N/A.

If leaked, forbidden to contact with strong oxidizers, mineral acids, strong alkalies, halogenated hydrocarbons.

## (1). Texicological information (套理性资料)

Signs & symptoms: None, unless battery ruptures.

In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.

Inhalation: Lung irritant. Skin contact: Skin irritant Eye contact: Eye irritant

Ingestion: Poisoning if swallowed

Medical conditions generally aggravated by exposure: In the event of exposure to internal contents, moderate to server irritation, burning and dryness of the skin may occur, Target organs nerves, liver and kidneys.

### 12: Ecological information (生态学资料)

Mammalian effects: None known at present.

Eco-toxicity: None known at present.

Bioaccumulation potential: Slowly Bio-degradable.

Environmental fate: None known environmental hazards at present.

### 13. Disposal consideration (废弃处置)

Do not incinerate, or subject cells to temperature in excess of 70°C, Such abuse can result in loss of seal leakage, and/or cell explosion. Dispose of in accordance with appropriate local regulations.

# 14. Transportinformation (运输信息

Label for conveyance: Lithium Battery Label.

Report No: 18PNS01159 01001

UN Number: UN3840 or UN3481

Packing Group: N/A EmS No: F-A, S-I Marine pollutant: No

Proper Shipping name: 1) Lithium ion batteries; 2) Lithium ion batteries packed with equipment; 3) Lithium ion batteries contained in equipment. (including Lithium ion polymer batteries)

Hazard Classification: The goods shall be complied with the requirements of Section II (or Section IB) of Packing Instructions 965~967 of 59th DGR Manual of IATA (2018 edition), including the passing of the UN38.3 test. And also complies with the Special Provision 188 of IMDG CODE (Amdt.37-16) 2016 Edition.

### 15. Regulation information (法规信息)

#### Law information

《Dangerous Goods Regulations》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous goods》

(Occupational Safety and Health Act) (OSHA)

《Toxic Substance Control Act》 (TSCA)

《Consumer Product Safety Act》(CPSA)

《Federal Environmental Pollution Control Act》 (FEPCA)

《The Oil Pollution Act》(OPA)

(Superfund Amendments and Reauthorization Act Title [[] (302/311/312/313))) (SARA)

《Resource Conservation and Recovery Act》 (RCRA)

《Safety Drinking Water Act》(CWA)

《California Proposition 65》

《Code of Federal Regulations》(CFR)

In accordance with all Federal, State and local laws.

### 16. Other information (其他信息)