

## 230V Industrial Dehumidifier, 900W, 50L

STOCK No. 12498 BRAND Draper

BARCODE 5059482061592

WARRANTY 12 months parts and labour

---

### FEATURES

- Capable of extracting up to 50L of moisture from the air per day
- Digital control panel features auto-defrost, auto-reset and 24-hour timer
- Onboard 7L condensation tank
- Includes 100cm x 11mm hose for continuous drainage
- Washable air filter
- Continuous drainage when connected to a hose or auto shut-off
- Wheels and handle for easy manoeuvrability
- Refrigerant R290 (propane based)



### DESCRIPTION

This large portable dehumidifier is capable of extracting up to 50L of moisture from the air per day. It is suitable for large spaces up to 120m<sup>2</sup> (minimum size - 10m<sup>2</sup>) to prevent the build-up of mildew and mould. It is equipped with a digital control panel and features auto-defrost, auto-reset and 24-hour timer. There is an onboard 7L condensation tank. The air filter is removable and washable for convenient cleaning. It automatically shuts off when the tank is full for manual drainage or choose continuous drainage (requires connection to a hose). The steel frame ensures high durability and long service life. Fitted with large wheels and a handle for easy manoeuvrability. Uses refrigerant R290 (propane based).

---

### CONTENTS

1 x 230V Industrial Dehumidifier, 900W, 50L

[Link to product - drapertools.com](https://www.drapertools.com)

## SPECIFICATIONS

|                               |  |
|-------------------------------|--|
| Voltage                       | 230V   |
| Power                         | 900W   |
| Extraction rate               | 50L per day (at 30°C, 80% relative humidity) |
| Target humidity range         | 10-95%                                       |
| Condensate tank capacity      | 7L   |
| Condensate tank outlet        | Ø11mm  |
| Weight                        | 30kg   |
| Dimensions                    | W 480 x H 655 x D 450mm                      |
| Ingress protection            | IP22   |
| Global warming potential      | 3  |
| Ambient operation environment | 5-35°C                                       |
| Minimum room size             | 10m <sup>2</sup>                             |
| Maximum discharge pressure    | 2.5Mpa                                       |
| Maximum suction pressure      | 1.0Mpa                                       |
| Refrigerant                   | R290 (propane), 200g                         |
| Discharge hose length         | 100cm  |
| Discharge hose outlet         | Ø11mm  |

## DOCUMENTS



Instruction Manual



Declaration Of  
Conformity UK CA



Declaration Of  
Conformity CE



Material Safety Data  
Sheet