

## Aluminium Oxide Bench Grinding Wheel, 200 x 25mm, 36 Grit

**STOCK No.** 99570 **BRAND** Draper

**BARCODE** 5010559995707

**WARRANTY** Consumable Warranty Applies



### FEATURES

- 200mm x 25mm x 36G
- Hard-wearing aluminium oxide
- 31.75mm bore and includes 5 reduction rings which enables compatibility with a most bench grinding tools (with a bore size between 12.7 - 31.75mm)
- General purpose grinding
- Dry cutting only
- Conforms to EN12413

### DESCRIPTION

A high-quality, hard-wearing aluminium oxide bench grinding wheel with coarse grit. Suitable for general grinding, deburring and tool sharpening on non-ferrous metals and steel. Dry-cutting use only. Manufactured with a 31.75mm bore and supplied with 5 reduction rings enabling each bench grinding wheel to fit most bench grinders with a bore size between 12.7 - 31.75mm.

**Conforms to EN12413.**

### CONTENTS

1 x Aluminium Oxide Bench Grinding Wheel, 200 x 25mm, 36 Grit

[Link to product - drapertools.com](https://www.drapertools.com)

**SPECIFICATIONS**

|                                      |                                                 |
|--------------------------------------|-------------------------------------------------|
| Diameter                             | 200mm                                           |
| Thickness                            | 25mm                                            |
| Grit                                 | 36G (Coarse)                                    |
| Metres Per Second                    | 35m/s                                           |
| Max Speed                            | 3,350rpm                                        |
| Bore                                 | 31.75mm                                         |
| Reduction Ring Sizes                 | 25.40mm / 22.23mm / 19.05mm / 15.90mm / 12.70mm |
| Wheel Hardness                       | P                                               |
| Approved Abrasive Wheel Marking Code | A36P 5V                                         |
| Certification                        | EN12413                                         |
| Nett Weight                          | 1.80kg                                          |