

## KNIPEX 13 46 165 SB VDE Stripping Pliers, 165mm

STOCK No. 14738 BRAND KNIPEX

BARCODE 5010559147380

**WARRANTY** Lifetime

## **FEATURES**

- · Multifunctional cutting and stripping with one pair of pliers
- For time-saving stripping of all round sheathed and damp-proof installation cables (e.g. NYM cable)
- Simplified access especially into deep mounted junction boxes thanks to slim head design and optimally angled cable sheath cutter
- Strip cables easily and without damage thanks to circular cutting edge with depth limiter
- Suitable for universal use: precision wire stripping holes for conductors from 1.5 and 2.5 mm<sup>2</sup>
- With side cutters for cutting and trimming conductors, wires, small screws and nails
- All cutting edges additionally induction-hardened to approx. 61 HRC for high wear resistance
- 30% lighter than comparable pliers



## **DESCRIPTION**

13 46 165 SB Stripping Pliers Multifunctional - cutting and stripping with one pair of pliers. for time-saving stripping of all round sheathed and dampproof installation cables (e.g. NYM cable). simplified access especially into deep mounted junction boxes thanks to slim head design and optimally angled cable sheath cutter. strip cables easily and without damage thanks to circular cutting edge with depth limiter. Suitable for universal use: precision wire stripping holes for conductors from 1.5 and 2.5 mm². With side cutters for cutting and trimming conductors, wires, small screws and nails. All cutting edges additionally induction-hardened to approx. 61 HRC for high wear resistance. 30% lighter than comparable pliers. - Cutting capacities medium hard wire (diameter): Ø 3.2mm- Cutting capacities hard wire (diameter): Ø 2.2mm- Stripping capacities (diametre): 8 – 13mm- Stripping capacities in square millimetres: 0.75 — 1.5mm² / 2.5mm²- VDE tested: yes

Manufactured to DIN ISO 5745 Specifications. Tested to EN 60900

## **CONTENTS**

1 x KNIPEX 13 46 165 SB VDE Stripping Pliers, 165mm

Link to product - drapertools.com

Page 1 of 1