

## 110V SMD LED Tripod Site Light, 50W, 5500 Lumens

**STOCK No.** 03193 **BRAND** Draper

**BARCODE** 5059482047961

**WARRANTY** 12 months parts and labour



### FEATURES

- This 5,500 lumens tripod SMD LED site light is height adjustable 0.8-1.3m and gives an even spread of light through a beam angle of 100 degrees
- The colour temperature is 6,000 to 6,500K – cool white to daylight
- IP65 and IK06 rated and suitable for industrial use
- Made from cast aluminium, carbon steel and toughened glass
- Supplied with a 3m VDE cable and approved 110V plug

### DESCRIPTION

This 5,500 lumens telescopic tripod SMD LED site light gives an even spread of light through a beam angle of 100 degrees, with a colour temperature of 6,000 to 6,500K – cool white to daylight – meaning fewer shadows. Made from cast aluminium and toughened glass with bumpers for added protection, the slim tripod site light has a durable aluminium die-cast housing and is adjustable to a maximum extended height of 1.3m, with a minimum lowered height of 0.8m. The site light is suitable for industrial use and is IP65 and IK06 rated. It comes supplied with a 3m VDE cable and an approved 110V plug. This 5,500 lumens telescopic tripod SMD LED site light is part of a wide range of SMD LED site lights available from Draper Tools.

**Manufactured and certified to UKCA, CE**

### CONTENTS

1 x 110V SMD LED Tripod Site Light, 50W, 5500 Lumens

[Link to product - drapertools.com](https://www.drapertools.com)

**SPECIFICATIONS**

|                     |                         |
|---------------------|-------------------------|
| Voltage             | 110V                    |
| Wattage             | 50                      |
| Brightness          | 5,500 lumens            |
| Product dimensions  | W 400 x H 700 x D 150mm |
| Lens size           | W 174.8 x H 98mm        |
| Max extended height | 1.785m                  |
| Min lowered height  | 0.912m                  |
| Beam angle          | 100°                    |
| Colour temperature  | 6,000–6,500K            |
| Weight              | 3.2kg                   |

---

**DOCUMENTS**



Instruction Manual