

Draper Expert Semi Automatic Tyre Changer with Assist Arm

STOCK No. 78612 **BRAND** Draper Expert

BARCODE 5010559786121

WARRANTY 12 months parts and labour

FEATURES

.



DESCRIPTION

Semi-automatic tyre changer, capable of removing and replacing tyres on wheels up to 26". Fitted with an assist arm (also known as a third arm) to aid the user when changing low profile and run flat tyres. The fully motorised turntable, pneumatically operated clamping jaws, powerful pneumatic bead breaker and tilt column enables the changing of low profile and run flat tyres quickly and easily. The self-centering four-jaw chuck, controlled by two clamping cylinders, always ensures wheel rims are correctly clamped. Alloy rims are treated particularly gently as the mounting head is provided with plastic protectors. The bead breaker is attached with a large anti-skid rubber pad, which preserves the tyres and rims. The machine is operated from a standard 13amp 3 pin plug. Supplied with the following accessories: tyre lever, filter regulator lubricator to connect your compressed air supply, alloy rim protectors, head tongue protectors and inflation gun and air hose.

Please note, this product now includes installation in the price, so let us help you to get set up in your garage or workshop. Postcode restrictions apply. Suitable for dry, flat, level, oil/grease free concrete surfaces' only, capable of supporting the weight of the machine - If area is deemed unsuitable at time of installation, call out charges will apply.

Full self-assembly and self-installation is required or warranty maybe invalid. Installation is included in the price. If you wish to discuss installation requirements then please email installation@drapertools.com. Please ensure you have adequate facilities to unload.

CONTENTS

1 x Semi Automatic Tyre Changer with Assist Arm

[Link to product - drapertools.com](https://www.drapertools.com)

SPECIFICATIONS

Bead Breaker Force	2100kg
Dimensions	1900 x 1950 x 1650mm
Max Wheel Diameter	45"
Motor	1.1KW
Pneumatic Supply	90 - 115psi (6-8BAR)
Power Supply	230V
For Rim Diameter (External Locking)	12" to 25"
For Rim Diameter (Internal Locking)	13" to 26"
Suitable For Use On Wheel Width	3" to 18"
Weight	350kg

DOCUMENTS



Instruction Manual



Parts Listing



Declaration Of
Conformity UK CA



Declaration Of
Conformity CE