

## SMD LED Rechargeable Tripod Site Light, 20W, 2000 Lumens, USB Cable Supplied

**STOCK No.** 03186 **BRAND** Draper

**BARCODE** 5059482047923

**WARRANTY** 12 months parts and labour

---

### FEATURES

- Made from cast aluminium, ABS plastic and toughened glass
- Lightweight height adjustable tripod (800-1500mm)
- Three independent adjustable lights (180° and 360°)
- Detachable light unit with magnetic base and hanging hook
- Made from cast aluminium, carbon steel and toughened glass
- IPX4 protection rating



---

### DESCRIPTION

This 2,000 lumens rechargeable SMD LED slim tripod site light creates 180 and 360-degree ultra-bright white or warm light (colour temperature 2,500-7,000K). Portable and easy to set up, the multi-angle rotational light has a beam angle of 66 degrees and beam distance of 55m, and it features high, medium and low settings. The lightweight aluminium tripod is extendable between 0.8m and 1.5m. The detachable light unit is made from die-cast aluminium and toughened glass and has a magnetic base and hanging hook for use where space is limited. The light is suitable for indoor and outdoor applications and is IP65 and IK07 rated. The built-in 3.7V 4,000mAh lithium battery has a runtime of 1.5 hours on 2,000 lumens, 2.5 hours on 1,200 lumens and 4.5 hours on 700 lumens and is rechargeable in five to six hours. The site light features a battery level indicator and comes with a 2m USB charging lead and can be used while it is charging. This site light is part of a wide range of LED site lights available from Draper Tools.

**Manufactured and certified to UKCA, CE**

---

### CONTENTS

1 x 2m USB-C charging lead

[Link to product - drapertools.com](https://www.drapertools.com)

**SPECIFICATIONS**

Wattage	20
Brightness	2,000 lumens
Dimensions (folded away)	W 80 x H 665 x D 80mm
Lens size	W 930 x H 350mm
Max extended height	1.5m
Min lowered height	0.8m
Beam angle	100°
Beam distance	55m
Colour temperature	2,500–7,000K
Runtime 2,000 lumens	1.5 hours
Runtime 1,200 lumens	2.5 hours
Runtime 700 lumens	4.5 hours
Charge time	5–6 hours
Weight	1.95kg

**DOCUMENTS**



Declaration Of  
Conformity UK CA



Declaration Of  
Conformity CE



Material Safety Data  
Sheet