

## Aluminium Oxide Bench Grinding Wheel, 150 x 16mm, 60 Grit

**STOCK No.** 99565 **BRAND** Draper

**BARCODE** 5010559995653

**WARRANTY** Consumable Warranty Applies

### FEATURES

- 150mm x 16mm x 60G
- Hard-wearing aluminium oxide
- 31.75mm bore and includes 5 reduction rings which enables compatibility with a most bench grinding tools (with a bore size between 12.7 - 31.75mm)
- General purpose grinding
- Dry cutting only
- Conforms to EN12413



### DESCRIPTION

A high-quality, hard-wearing aluminium oxide bench grinding wheel with fine grit. Suitable for general grinding, deburring and tool sharpening on non-ferrous metals and steel. Dry-cutting use only. Manufactured with a 31.75mm bore and supplied with 5 reduction rings enabling each bench grinding wheel to fit most bench grinders with a bore size between 12.7 - 31.75mm. Compatible with Draper Bench Grinder.

**Conforms to EN12413.**

### CONTENTS

1 x Aluminium Oxide Bench Grinding Wheel, 150 x 16mm, 60 Grit

[Link to product - drapertools.com](https://www.drapertools.com)

SPECIFICATIONS

|                                      |                                                 |
|--------------------------------------|-------------------------------------------------|
| Diameter                             | 150mm                                           |
| Thickness                            | 16mm                                            |
| Grit                                 | 60G (Fine)                                      |
| Metres Per Second                    | 35m/s                                           |
| Max Speed                            | 4,450rpm                                        |
| Bore                                 | 31.75mm                                         |
| Reduction Ring Sizes                 | 25.40mm / 22.23mm / 19.05mm / 15.90mm / 12.70mm |
| Wheel Hardness                       | M                                               |
| Approved Abrasive Wheel Marking Code | A60M 5V                                         |
| Certification                        | EN12413                                         |
| Nett Weight                          | 0.63kg                                          |