



# SAFETY DATA SHEET

Version No.2

Revision date: 18/07/23

## 1. Identification of the Substance/Mixture and of the Company/Undertaking

### 1.1 Product Identifier:

Trade name:  
41922 Carb Cleaner

### 1.2 Relevant Identified Uses:

Car maintenance product. PC35 Washing and cleaning products

### 1.3 Details of the Supplier of the Safety Data Sheet:

**Company name:** Draper Tools Ltd  
**Address:** Hursley Road, Chandler's Ford  
Eastleigh, Hampshire SO53 1YF  
**Telephone:** +44 (0) 23 80266355  
**Email:** sales@drapertools.com  
**Contact person:** Customer Service  
**Website:** www.drapertools.com

### 1.4 Emergency Telephone Number:

+44 (0) 23 80266355 (not 24hrs)

## 2. Hazards Identification

### 2.1 Classification of the substance or mixture:

#### 2.1.2 Classification (EC 1272/2008)

#### Physical hazards:

Aerosol 1 - H222, H229

#### Health hazards:

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H336 STOT RE 2 - H373

#### Environmental hazards:

Aquatic Chronic 3 - H412

#### Human health:

Gas or vapour is harmful on prolonged exposure or in high concentrations. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal. Vapours and spray/mists in high concentrations are narcotic.

#### Environmental:

The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

#### Physicochemical:

Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

### 2.2 Label Elements:

#### Hazard pictograms



**Signal word:**  
Danger

#### Hazard statements:

H222 Extremely flammable aerosol  
H229 Pressurised container: may burst if heated  
H315 Causes skin irritation  
H319 Causes serious eye irritation  
H336 May cause drowsiness or dizziness  
H373 May cause damage to organs through prolonged or repeated exposure  
H412 Harmful to aquatic life with long lasting effects

#### Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source  
P251 Do not pierce or burn, even after use  
P260 Do not breathe vapour/ spray  
P271 Use only outdoors or in a well-ventilated area

## 2. Hazards Identification

### Precautionary statements :

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F  
P102 Keep out of reach of children  
P262 Do not get in eyes, on skin, or on clothing  
P501 Dispose of contents/ container in accordance with local regulations.

### Supplemental label information :

EUH066 Repeated exposure may cause skin dryness or cracking.RCH002b For professional users only.

### Contains:

ACETONE, HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, XYLENE

### Detergent labelling:

≥ 30% aliphatic hydrocarbons, 15 - < 30% aromatic hydrocarbons

### 2.3 Other hazards:

This product does not contain any substances classified as PBT or vPvB.

## 3. Composition/Information on Ingredients

### 3.2. Mixtures

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS	30-60%
CAS number: 68476-85-7	EC number: 270-704-2

Classification
Flam. Gas 1A - H220
Press. Gas (Liq.) - H280

ACETONE	10-30%
CAS number: 67-64-1	EC number: 200-662-2 REACH registration number: 01- 2119471330-49

Classification
Flam. Liq. 2 - H225
Eye Irrit. 2 - H319
STOT SE 3 - H336

HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	10-30%
CAS number: -	EC number: 921-024-6 REACH registration number: 01-2119475514-35

Classification	
Flam. Liq. 2 - H225	Asp. Tox. 1 - H304
Skin Irrit. 2 - H315	Aquatic Chronic 2 - H411
STOT SE 3 - H336	

XYLENE	10-30%
CAS number: 1330-20-7	EC number: 215-535-7 REACH registration number: 01-2119488216-32- XXXX

Classification		
Flam. Liq. 3 - H226	Skin Irrit. 2 - H315	STOT RE 2 - H373
Acute Tox. 4 - H312	Eye Irrit. 2 - H319	Asp. Tox. 1 - H304
Acute Tox. 4 - H332	STOT SE 3 - H335	Aquatic Chronic 3 - H412

### 3. Composition/Information on Ingredients

ETHYLBENZENE CAS number: 100-41-4	EC number: 202-849-4	REACH registration number: 01-2119489370-35	1-5%
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H332 STOT RE 2 - H373			
Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412			
TOLUENE CAS number: 108-88-3	EC number: 203-625-9	REACH registration number: 01-2119471310-51	<1%
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d			
STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304			
HEXANE-norm CAS number: 110-54-3	EC number: 203-777-6	REACH registration number: 01-2119480412-44	<1%
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361f STOT SE 3 - H336			
STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			

The full text for all hazard statements is displayed in Section 16.

### 4. First Aid Measures

#### 4.1 Description of first aid measures:

##### General information :

Move affected person to fresh air at once.

##### Eye Contact:

Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

##### Skin Contact:

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

##### Ingestion:

Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.

##### Inhalation:

If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed:

##### General information :

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

#### 4.3 Indication of any immediate medical attention and special treatment needed

##### Notes for the doctor :

Treat symptomatically.

## 5. Fire Fighting Measures

---

### 5.1 Suitable Extinguishing Media:

Extinguish with foam, carbon dioxide, dry powder or water fog.

### 5.2 Special hazards arising from the substance or mixture:

Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Extremely flammable. Forms explosive mixtures with air.

### 5.3 Advice for Fire Fighters.

#### Protective actions during

Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Warn firefighters that aerosols are involved. Use water to keep fire exposed containers cool and disperse vapours.

## 6. Accidental Release Measures

---

### 6.1 Personal precautions, protective equipment and emergency procedures:

#### Personal precautions

Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours.

### 6.2 Environmental precautions:

#### Environmental precautions

Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material.

### 6.3 Methods and Materials for Containment and Clean Up:

#### Methods for cleaning up

Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb spillage with inert, damp, non-combustible material.

### 6.4 Reference to other sections:

#### Reference to other sections

For personal protection, see Section 8. For waste disposal, see Section 13..

## 7. Handling and Storage

---

### 7.1 Precautions for safe handling:

#### Usage precautions

Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Do not spray on a naked flame or any incandescent material. Eliminate all sources of ignition.

### 7.2 Conditions for safe storage, including any incompatibilities:

#### Storage precautions

Keep away from heat, sparks and open flame. Store at moderate

temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Extremely flammable.

#### Extremely flammable

Store in tightly-closed, original container in a dry, cool and well ventilated place.

### 7.3 Specific end use(s):

#### Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

## 8. Exposure Controls/Personal Protection

---

### 7.1 Control parameters:

#### Occupational exposure limits

##### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

#### ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

#### HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Long-term exposure limit (8-hour TWA): WEL 1200 mg/m<sup>3</sup>

## 8. Exposure Controls/Personal Protection

---

### XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m<sup>3</sup>

Sk

### ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 441 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 125 ppm(Sk) 552 mg/m<sup>3</sup>(Sk)

### TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m<sup>3</sup>

Sk

### HEXANE-norm

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

**Ingredient comments :** WEL = Workplace Exposure Limits.

### XYLENE (CAS: 1330-20-7)

Biological limit values

650 mmol/mol creatinine Medium : urine

Sampling time: post-shift

Parameter: methylhippuric acid

### DNEL

Consumer - Oral; Long term systemic effects: 12.5 mg/kg/day

Consumer

- Dermal; Long term systemic effects: 1872 mg/kg/day

Consumer

- Inhalation; Long term systemic effects: 65.3 mg/m<sup>3</sup>

Consumer

- Inhalation; Short term : 260 mg/m<sup>3</sup>

Industry

- Dermal; Long term systemic effects: 3182 mg/kg/day

Industry

- Inhalation; Long term systemic effects: 221 mg/m<sup>3</sup>

Industry

- Inhalation; Short term : 442 mg/m<sup>3</sup>

### PNEC

This product is a UVCB substance and its composition will be variable, so reported properties may vary or require a range of values to describe them

- Fresh water; 0.327 mg/l

- marine water; 0.327 mg/l

- Intermittent release; 0.327 mg/l

- STP; 6.58 mg/l

- Sediment (Freshwater); 12.46 mg/kg

- Sediment (Marinewater); 12.46 mg/kg

- Soil; 2.31 mg/kg

### ETHYLBENZENE (CAS: 100-41-4)

#### DNEL

Consumer - Oral; Long term systemic effects: 1.6 mg/kg/day

Consumer

- Dermal; Long term systemic effects: 108 mg/kg/day

Consumer

- Inhalation; Long term systemic effects: 14.8 mg/m<sup>3</sup>

Industry

- Dermal; Long term systemic effects: 180 mg/kg/day

Industry

- Inhalation; Long term systemic effects: 77 mg/m<sup>3</sup>

Industry

- Inhalation; Short term : 289 mg/m<sup>3</sup>

#### PNEC

Fresh water; 0.1 mg/l

marine water; 0.1 mg/l

Intermittent release; 0.1 mg/l

Sediment (Freshwater); 13.7 mg/kg

Sediment (Marinewater); 13.7 mg/kg

Soil; 2.68 mg/kg

STP; 9.6 mg/kg

### TOLUENE (CAS: 108-88-3)

#### DNEL

General population - Inhalation; : 226 mg/m<sup>3</sup>

#### PNEC

- Fresh water; 0.68 mg/l

- marine water; 0.68 mg/l

- Soil; 2.89 mg/kg

### 8.2 Exposure controls

#### Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

#### Personal protection

Do not eat, drink or smoke when using this product.

## 8. Exposure Controls/Personal Protection

---

### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

### Hand protection

Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). The most suitable glove should be

chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

### Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin.

### Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

## 9. Physical and Chemical Properties

---

### 9.1 Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Clear.
Odour	Organic solvents.
Initial boiling point and range	-40 to -2°C @ 1013 hPa
Flash point	< -40°C Closed cup.
Upper/lower flammability or explosive limits	Lower flammable/ explosive limit: 1.8% Upper flammable/ explosive limit: 9.5%

Vapour pressure	ca. 590 to 1760 kPa @ 45°C
Vapour density	ca. 1.5 at 15°C
Auto-ignition temperature	410-580°C
Comments	Information given is applicable to the major ingredient.

### 9.2 Other information

Other information :	Not available
Volatile organic compound :	This product contains a maximum VOC content of 657 g/l.

## 10. Stability and Reactivity

---

<b>10.1 Reactivity:</b>	Stable at normal ambient temperatures and when used as recommended.
<b>10.2 Chemical Stability:</b>	Avoid the following conditions: Heat, sparks, flames.
<b>10.3 Hazardous Reactions:</b>	Does not decompose when used and stored as recommended.
<b>10.4 Conditions of avoid:</b>	Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.
<b>10.5 Incompatible materials:</b>	Keep away from oxidising materials, heat and flames.

### 10.6 Hazardous Decomposition Products:

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.

## 11. Toxicological Information

---

### 11.1 Information on toxicological effects:

Acute toxicity - dermal ATE dermal (mg/kg)	5,500.0	Eye contact Irritating to eyes.	Vapour or spray in the eyes may cause irritation and smarting.
Acute toxicity - inhalation ATE inhalation (vapours mg/l)	55.0	Acute and chronic health hazards	Arrhythmia (deviation from normal heart beat). Irritating to skin. Irritating to eyes. Narcotic effect.
General information	Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.	Route of exposure	Inhalation
Inhalation	Vapours and spray/mists in high concentrations are narcotic. Unconsciousness, possibly death.	Target organs	Central nervous system Respiratory system, lungs
Skin contact	Harmful in contact with skin.	Medical symptoms	Skin irritation. Arrhythmia (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness. Irritation of eyes and mucous membranes.

## 12. Ecological Information

---

### Ecotoxicity:

**ENVIRONMENTAL HAZARDS:** This product has not been tested but contains ingredients which are harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment. During normal use the volatility of the components and the packaging form, pressurised container, make entry into the aquatic environment unlikely, however, do not empty or discharge into drains or watercourses. Ensure container is empty before disposal to prevent contents entering watercourses.

**12.1 Toxicity:** Not available.

**12.2 Persistence and Degradability:** Not available.

**12.3 Bio Accumulative Potential:** Not available.

**12.4 Mobility in soil** Not available.

**12.5 Results of PBT and vPvB assessment:** Not available.

**12.6 Other adverse effects** Not available.

## 13. Disposal Considerations

---

### 13.1 Waste treatment methods:

#### General information

Do not puncture or incinerate, even when empty.

Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion.

#### Disposal methods

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

## 14. Transport Information

---

### General:

This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.

### 14.1 UN number:

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

## 14. Transport Information

### 14.2 UN proper shipping name:

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

### 14.3 Transport hazard class(es):

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels:



### 14.4 Packing group:

ADR/RID packing group	None
IMDG packing group	None
ICAO packing group	None
ADN packing group	None

### 14.5 Environmental hazards:

Environmentally hazardous substance/marine pollutant No.

### 14.6 Special precautions for user:

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## 15. Regulatory Information

### 15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture:

#### National regulations:

Control of Substances Hazardous to Health Regulations 2002 (as amended).

EH40/2005 Workplace exposure limits.

The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

#### Guidance:

Workplace Exposure Limits EH40.

Safety Data Sheets for Substances and Preparations.

Approved Classification and Labelling Guide (Sixth edition) L131.

British Aerosol Manufacturers Code of Practice 7th. Edition 1999

### 15.2 Chemical Safety Assessment:

No chemical safety assessment has been carried out.

## 16. Other Information

Hazard statements in full:

- H220 Extremely flammable gas
- H222 Extremely flammable aerosol
- H225 Highly flammable liquid and vapour
- H226 Flammable liquid and vapour
- H229 Pressurised container: may burst if heated
- H280 Contains gas under pressure; may explode if heated
- H304 May be fatal if swallowed and enters airways
- H312 Harmful in contact with skin
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness
- H361d Suspected of damaging the unborn child

- H361f Suspected of damaging fertility
- H373 May cause damage to organs through prolonged or repeated exposure
- H411 Toxic to aquatic life with long lasting effects
- H412 Harmful to aquatic life with long lasting effects

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability of such information for their own particular use.