

Bandsaw, 340mm, 1100W

STOCK No. 84715 BRAND Draper

BARCODE 5010559847150

WARRANTY 24 months parts and labour

FEATURES

- · Two-speed operation control
- · Adjustable blade tensioning and tracking for precise cutting
- Mitre guide for crosscut work. Graduated to 30 degrees for both left and right hand angles
- Table tilting with 0-45 degree range
- · Fitted with LED worklight and convenient tool drawer in base unit
- For angled cutting, ripping, mitre and bevel cutting
- Fitted with a cable and approved plug
- · Supplied with blade, mitre gauge, rip fence and dust extraction outlet
- Can be bench mounted or fitted to a stand (available separately)
- · Excellent performance and cutting capacity



DESCRIPTION

This two-speed bandsaw is designed to cut wood, wood derived materials and plastics. Built to a high specification and ideal for trade professionals. This is reflected in the quality of the structure and strength of the worktable support and tilt mechanism, as well as the structure and strength of the blade wheel adjusting mechanism. The adjustable blade tensioning and tracking allows for precise cutting. There is a high spec mitre guide for crosscut work. The strong table tilts with a 0-45 degree range allowing angled cutting, ripping and mitre and bevel cutting. No-volt release switch prevents uncontrolled blade to re-start after power interruption. There is a tool drawer built into the base unit providing convenient storage while working. Supplied with 4tpi blade, parallel rip fence and other accessories. This bandsaw can be floor standing or mounted on a stand available separately (Stock No. 99270).

No-volt switch

CONTENTS

- 1 x 4tpi blade
- 1 x Parallel rip fence
- 1 x Open ended spanner
- 1 x Push stick
- 4 x Hex keys
- 4 x Pan head screw, M7 x 12mm
- 4 x Washers, 8.5mm
- 4 x Plastic wing bolts

Link to product - drapertools.com



SPECIFICATIONS

Weight	74kg
Bandsaw dimensions	850 x 650 x 1297mm
Table size	545 x 515mm (Tilt to 45 degrees)
Cutting speed	2 speed, 6.16m/sec (370m/min) and 13.33m/sec (800m/min)
Maximum capacity	205mm
Cutting depth	225mm
Maximum throat capacity	340mm
No load speed	1400rpm
Input	1100W
Frequency	50Hz
Voltage	230V

DOCUMENTS







Parts Listing



Declaration Of Conformity UK CA



Declaration Of Conformity CE

Created: 11/10/25