

SAFETY DATA SHEET

Product Name: RECHARGEABLE LITHIUM-ION CELL

Review Date: 01 JAN 2021

SECTION 1 Product and Company Identification

PRODUCT NAME: RECHARGEABLE LITHIUM-ION CELL

3.6V 2000mAh 7.2Wh

APPLICATIONS: For Stock No.03509 D20 BRUSHED MOTOR COMBI DRILL SET

SUPPLIER: Draper Tools Ltd

Hursley Road
Chandlers Ford
Eastleigh
Hampshire
SO53 1YF

Draper Helpline +44 (0) 2380 494344
Opening hours 8:30-17:00 Monday – Friday.

SECTION 2 Hazard Description

Hazard class and label elements of the product according to Regulation (EC) No. 1272/2008

[EU-GHS/CLP]:

GHS HAZARD CLASS

Non-hazardous substance or mixture.

Material Safety Data Sheet

MSDS No.: EMS.210.101.004.BES	Initial Date: Jan. 01, 2021	Version: 1.0
Product Name: Rechargeable Lithium-ion Cell	Revision Date: Jan. 01, 2021	Item No.: 20A373A121

GHS label elements

Pictogram(s):	None
Signal word:	None

Hazard statements

	Not applicable.
--	-----------------

Other Hazards

	None.
--	-------

Hazard description

◆ Physical and chemical hazards

	Non-flammable, no special combustion and explosion characteristics.
--	---

◆ Health hazards

Inhalation:	Cough, headache, fatigue, sleepiness.
Ingestion:	Burning sensation, headache, vague consciousness, dizziness and confusion.
Skin contact:	Redness, burning.
Eye contact:	Redness, pain, burning.

◆ Environmental hazards

	Please refer to Section 12 of MSDS.
--	-------------------------------------

Section 3

Composition/Ingredient Data

Material

Mixture

Component(s)	Content, %	CAS No.	EC No.
Nickel cobalt lithium manganate	26-40	Proprietary	Proprietary
Steel shell and inert components	14-22	N/A	N/A
Graphite	13-21	7782-42-5	231-955-3
Organic electrolyte	10-18	Proprietary	Proprietary

Material Safety Data Sheet

MSDS No.: EMS.210.101.004.BES	Initial Date: Jan. 01, 2021	Version: 1.0
Product Name: Rechargeable Lithium-ion Cell	Revision Date: Jan. 01, 2021	Item No.: 20A373A121

Component(s)	Content, %	CAS No.	EC No.
Copper	7-15	7440-50-8	231-159-6
Aluminum	3-7	7429-90-5	231-072-3

Section 4 First Aid Measures

Description of first aid measures

General advice:	Show this material safety data sheet to the doctor in attendance. After receiving the first-aid measure required, consult a physician if necessary.
Skin contact:	Remove contaminated clothing and shoes. Wash off with mild soap and plenty of water. If skin irritation occurs or persists, consult a physician immediately.
Eyes contact:	Check for and remove any contact lenses, occasionally lifting the upper and lower eyelids. Immediately flush eyes with running water, disappear until the chemical residues so far. Provide a readily-accessible eyewash facility and quick-drench safety shower. Do not rubbing eyes with hand. If eye irritation occurs or persists, consult a physician immediately.
Inhalation:	Move exposed person to fresh air. Maintain an open airway. Keep person warm and at rest. If breathing is irregular, provide artificial respiration or oxygen by trained personnel. Get medical attention if adverse health effects persist or are severe.
Ingestion:	Wash out mouth with water. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person.

Most important acute and delayed symptoms/effects

1	The most important known symptoms and effects are described in section 2 and/or in section 11.
---	--

Material Safety Data Sheet

MSDS No.: EMS.210.101.004.BES

Initial Date: Jan. 01, 2021

Version: 1.0

Product Name: Rechargeable Lithium-ion Cell

Revision Date: Jan. 01, 2021

Item No.: 20A373A121

Immediate/special treatment

- 1 Continue with first aid measures. Treat symptomatically and supportively.
- 2 Symptoms may be delayed.

Section 5 Firefighting Measures

Extinguishing agent

Suitable/Unsuitable
extinguishing agents:

In case of fire, water flooded ground fire. If the battery is burning, water may not be extinguished, but can use water cooling adjacent batteries so as to control the spread of fire. The preferred medium for small fire is carbon dioxide, dry powder, or foam extinguishing agent, but for the lithium battery is burning may be no use, the battery will burn until complete combustion. In fact, all lithium batteries can be controlled by water. However, when using water to produce hydrogen gas may be mixed with air to form explosive mixture. LITH-X (graphite powder) or copper powder fire extinguishers, sand, dry, powdered dolomite or soda can be used as smothering agent

Special hazards arising from the substance or mixture

- 1 If this product is involved in a fire, the following can be released: Carbon oxides, metal oxides, etc.

Fire precautions and measures

- 1 Firefighters must wear self-contained breathing apparatus, wear full body fire suit, fire extinguishing in the upwind.
- 2 As far as possible will be transferred to empty containers from the scene.
- 3 Keep the fire water spray containers cooling, until the end of fire.
- 4 If the containers in the fire ground have been color, must be evacuated immediately.
- 5 Isolated accident scene, prohibit access.
- 6 Receiving and processing of fire, to prevent environmental pollution.

Section 6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

- 1 No action shall be taken involving any personal risk or without suitable training.

Material Safety Data Sheet

MSDS No.: EMS.210.101.004.BES

Initial Date: Jan. 01, 2021

Version: 1.0

Product Name: Rechargeable Lithium-ion Cell

Revision Date: Jan. 01, 2021

Item No.: 20A373A121

- | | |
|---|---|
| 2 | Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. |
| 3 | Do not touch or walk through spilt material, avoid slipping. |
| 4 | Avoid breathing steam. |
| 5 | Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. |
| 6 | Put on appropriate personal protective equipment (see section 8). |

Environmental precautions

- | | |
|---|---|
| 1 | Prevent further leakage or spillage if safe to do so. |
| 2 | Discharge into the environment must be avoided. |

Methods and materials for containment and cleaning up

- | | |
|---|--|
| 1 | <p>Small spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.</p> <p>Large spill: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth.</p> |
| 2 | Contaminated absorbent material may pose the same hazard as the spilt product. |
| 3 | Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations. |

Section 7 Handling and Storage

Precautions for safe handling

- | | |
|---|---|
| 1 | Don't use or leave the battery near a heat source as fire or heater. |
| 2 | If the battery gives off an odor, generates heat, becomes discolored or deformed, or in any way appear abnormal during use or storage, immediately remove it from the device and stop using. |
| 3 | Don't put the battery excessive vibration, avoid short circuit, however accidental short circuit for a short period of time will not have a serious impact on the battery. |
| 4 | Long-term short circuit can make battery loss of energy, generate a lot of heat burn skin, and even cause a fire or explosion. |
| 5 | Chaos of the battery in bulk in containers, coins, metal accessories, metal workbench, covered by or metal belt and so on battery device can be used for assembly is the source of cause a short-circuit. |

Material Safety Data Sheet

MSDS No.: EMS.210.101.004.BES	Initial Date: Jan. 01, 2021	Version: 1.0
Product Name: Rechargeable Lithium-ion Cell	Revision Date: Jan. 01, 2021	Item No.: 20A373A121

6	Transport or storage battery should have effective measures of prevent short circuit.
7	Don't disassembly or damage to the battery.
8	Keep away from heat/sparks/open flames/hot surfaces.
9	Handling carefully to prevent damage the packaging and container.
10	Equipped with corresponding varieties and number of fire equipment and spill contingency processing equipment.

Precautions for storage

1	Stored in a cool, dry and ventilated place, may cause the battery performance loss under high temperature, leakage, rust.
2	Don't expose the battery under the open flame, stored away from water and strong oxidizing agent.
3	Equipped with corresponding varieties and number of fire equipment and spill contingency processing equipment.
4	Keep out of reach of children and pets.

Section 8

Exposure Controls/Personal Protection

Control parameters

◆ Occupational Exposure limit values

Components CAS No.	Country/region	Occupational exposure limits (8h)		Occupational exposure limits (Short time)	
		ppm	mg/m ³	ppm	mg/m ³
Aluminum 7429-90-5	USA-OSHA	-	15	-	-
	Korea	-	10	-	-
	Ireland	-	1	-	-
	Germany (DFG)	-	4	-	-
	Denmark	-	5	-	10
	Australia	-	10	-	-
Copper 7440-50-8	Netherlands	-	0.1	-	-
	Poland	-	0.2	-	-
	Latvia	-	0.5	-	1

Material Safety Data Sheet


MSDS No.: EMS.210.101.004.BES	Initial Date: Jan. 01, 2021	Version: 1.0
Product Name: Rechargeable Lithium-Ion Cell	Revision Date: Jan. 01, 2021	Item No.: 20A373A121

	Germany (DFG)	-	0.01	-	0.02
--	---------------	---	------	---	------

Engineering controls

- 1 Ensure adequate ventilation, especially in confined areas.
- 2 Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

General requirements:	
Respiratory protection:	Respiratory protective equipment is not necessary if used as intended. Respiratory protection may be required under exceptional circumstances when excessive air contamination exists. If the batteries leaks must try to keep the air circulation, avoid operating in a narrow place.
Eye protection:	Not necessary if used as intended, wear goggles/safety glasses giving complete eye protection if the battery damaged or leaking.
Skin and body protection:	Not necessary if used as intended, wear appropriate clothing and boots to minimize skin exposure if the battery damaged or leaking.
Hands protection:	Not necessary if used as intended, wear appropriate protective gloves if the battery damaged or leaking. Check protective gloves prior to each use for their proper condition. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Section 9

Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance and character:	Violet cylinder plastics film shell
Odor:	Odorless
Flash point (°C):	No data
Melting point/freezing point (°C):	No data
Initial boiling point and boiling range (°C):	No data

Material Safety Data Sheet

MSDS No.: EMS.210.101.004.BES

Initial Date: Jan. 01, 2021

Version: 1.0

Product Name: Rechargeable Lithium-ion Cell

Revision Date: Jan. 01, 2021

Item No.: 20A373A121

Evaporation rate:	No data
Steam pressure (20°C):	No data
Relative density (water=1):	No data
Partition coefficient: n-octanol/water:	No data
Decomposition temperature (°C):	No data
pH value:	No data
Auto ignition temperature (°C):	No data
Explosion limit [% (v/v)]:	Non explosives
Relative vapor density(air=1):	No data
Solubility:	Insoluble in water
Flammability (solid, gas):	Non-flammable
Oxidizing properties:	The substance does not belong to oxidizing substances

Section 10 Stability and Reactivity

Stability and Reactivity

Stability:	The product is chemically stable.
Reactivity:	Stable under recommended storage and handling conditions.
Incompatible materials:	Strong oxidizing agents, strong acids and strong bases.
Conditions to avoid:	In contrast to the nature of the material, overheating, exposed to damp air or water, mechanical vibration and power abuse.
Hazardous decomposition products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11 Toxicological Information

Material Safety Data Sheet

MSDS No.: EMS.210.101.004.BES

Initial Date: Jan. 01, 2021

Version: 1.0

Product Name: Rechargeable Lithium-ion Cell

Revision Date: Jan. 01, 2021

Item No.: 20A373A121

Toxicological Information

Acute toxicity:	No data.
Skin corrosion/irritation:	According to the existing data, the product is not classified.
Eye corrosion/irritation:	Irritating effect possible.
Respiratory sensitization:	These products are not known to cause human respiratory sensitization.
Skin sensitization:	These products are not known to cause skin sensitization.
Germ cell mutagenicity:	According to the existing data, the product is not classified.
Carcinogenicity:	No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.
Reproductive toxicity:	According to the existing data, the product is not classified.
Specific target organ toxicity - single exposure:	According to the existing data, the product is not classified.
Specific target organ toxicity - repeated exposure:	According to the existing data, the product is not classified.
Aspiration hazard:	According to the existing data, the product is not classified.
Additional reproductive toxicity hazards:	According to the existing data, the product is not classified.

Section 12 Ecological Information

Aquatic toxicity

Acute/Chronic aquatic toxicity:	According to the existing data, the product is not classified.
---------------------------------	--

Persistence and degradability

Persistence:	No data.
--------------	----------

Bioaccumulative potential

Bioaccumulation:	No data.
------------------	----------

Mobility in soil

Mobility:	No data.
-----------	----------

Material Safety Data Sheet

MSDS No.: EMS.210.101.004.BES

Initial Date: Jan. 01, 2021

Version: 1.0

Product Name: Rechargeable Lithium-ion Cell

Revision Date: Jan. 01, 2021

Item No.: 20A373A121

Other adverse effects

Chemical name	CAS No.	Results of PBT and vPvB assessment
Nickel cobalt lithium manganate	Proprietary	Not belong to PBT/vPvB
Aluminum	7429-90-5	Not belong to PBT/vPvB
Graphite	7782-42-5	Not belong to PBT/vPvB
Copper	7440-50-8	Not belong to PBT/vPvB
Organic electrolyte	Proprietary	Not belong to PBT/vPvB

Section 13 Disposal Considerations

Waste disposal

Residual waste:	Before disposal should refer to the relevant national and local laws and regulation. The generation of waste should be avoided or minimized wherever possible. Recommended transfer to a suitable container and arrange for collection by specialized disposal company if recycling is not feasible.
Contaminated packaging:	The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations:	Dispose of container and unused contents in accordance with national and local relevant regulations laws.

Section 14 Transport Information

Transport Information

UN No.:	UN3480 or UN3481
UN Transport name:	Lithium ion batteries or Lithium ion batteries contained in equipment
Hazard class(es) :	9
Packaging group:	N/A
Environmental hazard Marine pollutant	No

Material Safety Data Sheet

MSDS No.: EMS.210.101.004.BES	Initial Date: Jan. 01, 2021	Version: 1.0
Product Name: Rechargeable Lithium-ion Cell	Revision Date: Jan. 01, 2021	Item No.: 20A373A121

(Yes/No):	
ICAO/ATA:	Can be shipped by air in accordance with International Civil Aviation Organization (ICAO), TI or International Air Transport Association (IATA), DGR Packing Instructions (PI) 965 Section II or 967 Section II appropriate of IATA DGR 62 st (2021 Edition) for transportation.
IMDG CODE:	The batteries are not restricted to IMDG Code 2018 Edition (Amdt 39-18) according to special provision 188.
ADR/AND:	The batteries are not subject to the provisions of United Nations Economic Commission for Europe (UNECE) ADR/ADN if they meet the requirements of special provision 188 of Chapter 3.3. Applicable as from 1 January 2019.

In addition, to be permitted in transport each lithium cell and battery types must have passed the applicable tests set out in Subsection 38.3 of the UN Manual of Tests and Criteria.

Section 15 Regulatory Information

■ Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulatory information: Reference to the local, national, US, EU, CA and international regulations.

CAS No.	TSCA	IECSC	EINECS/ELINCS/NLP	DSL/NDSL
7429-90-5	Listed	Listed	Listed	Listed DSL
7782-42-5	Listed	Listed	Listed	Listed DSL
7440-50-8	Listed	Listed	Listed	Listed DSL

TSCA:	United States Toxic Substances Control Act Inventory
EINECS:	European Inventory of Existing Commercial Chemical Substances
DSL:	Canadian Domestic Substances List
IECSC:	China Inventory of Existing Chemical Substances
PICCS:	Philippines Inventory of Chemicals and Chemical Substances
NZIoC:	New Zealand Inventory of Chemicals
KECI:	Existing and Evaluated Chemical Substances

Material Safety Data Sheet

MSDS No.: EMS.210.101.004.BES	Initial Date: Jan. 01, 2021	Version: 1.0
Product Name: Rechargeable Lithium-Ion Cell	Revision Date: Jan. 01, 2021	Item No.: 20A373A121

AICS:	List of existing chemical substances in Australia
★Note:	“√” Indicates that the substance included in the regulations “×” That no data or included in the regulations

Section 16 Other Information

Abbreviations or phrases

ACGIH:	American Conference of Governmental Industrial Hygienists
ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS:	Chemical Abstracts Service
CLP:	Classification, labeling and packaging
EC:	Council of Europe
ECHA:	European Chemicals Agency
EINECS:	European Inventory of Existing commercial Chemical Substances
GHS:	Globally Harmonized System of Classification and Labelling of Chemicals
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association
RID:	Regulation for rail International transportation of Dangerous goods
ICAO:	International Civil Aviation Organization
IMDG:	International Maritime Dangerous Goods Code
IC ₅₀ :	Inhibitory Concern Triton 50%
LC ₅₀ :	Lethal Concentration 50%
LD ₅₀ :	Median Lethal Dose 50%
MAPROL:	International Convention for the Prevention of Pollution from Ships
REACH:	REGULATION concerning the Registration, Evaluation, Authorization and Restriction of Chemicals
STEL:	Short Term Exposure Limit
TWA:	Time Weighted Average
MAC:	Maximum Allowable Concentration

Material Safety Data Sheet

MSDS No.: EMS.210.101.004.BES	Initial Date: Jan. 01, 2021	Version: 1.0
Product Name: Rechargeable Lithium-Ion Cell	Revision Date: Jan. 01, 2021	Item No.: 20A373A121

OSHA:	Occupational Safety and Health Administration
NIOSH:	National Institute for Occupational Safety and Health
TLV:	Threshold Limit Value
TLV-TWA:	Threshold Limit Value-Time Weighted Average
TLV- STEL:	Threshold Limit Value-Short term Exposure Limit
PC-TWA:	Permissible Concentration-Time Weighted Average
PC-STEL:	Permissible Concentration-Short Term Exposure Limit
PEL:	Permissible Exposure Limit
OELs:	Occupational Exposure Limits

Reference

1	IARC
2	OECD: The Global Portal to Information on Chemical Substances
3	U.S. Department of Transportation: ERG
4	Germany GESTIS-database on hazard substance
5	CAMEO Chemicals
6	NLM: ChemIDplus
7	EPA: Integrated Risk Information System
8	IPCS: The International Chemical Safety Cards (ICSC)

Disclaimer

1	The above information is believed to be correct but we can not guarantee the absolute universality and accuracy and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product.
2	TUV-Laboratory ensures the objectivity and fairness of the test and fulfills the confidentiality obligations of the applicant's information. The applicant is responsible for the authenticity of the submitted samples and information. The results shown in this report relate only to the samples tested. The test results only reflect the evaluation of the sample being tested and are not used for other purposes. TUV-Laboratory shall not be liable for any loss arising from or in connection with this report, contract, tort, regulation or other reasons. This report is invalid or has been copied in whole or in part if there is no approver signature and TUV-Laboratory testing special seal. This report may not be published as an advertisement without the approval of the TUV-Laboratory. Any unauthorized

Material Safety Data Sheet

MSDS No.: EMS.210.101.004.BES

Initial Date: Jan. 01, 2021

Version: 1.0


Product Name: Rechargeable Lithium-ion Cell

Revision Date: Jan. 01, 2021

Item No.: 20A373A121

alteration, forgery or falsification of the content or appearance of this document is illegal and the offender may be prosecuted to the fullest extent of the law.

Product photo(s)



END OF REPORT