


Technical Data Sheet

General

Article number:
90672674

Description:
Undercoating Spray Gun with
adjustable Nozzle



Specification:

Gun for the application of undercoating and cavity protection products in tins of 1 L. With an air connection and a nozzle to apply the product on the surface. This gun is also equipped with an adjustable nozzle to adapt the spray pattern (orange peel effect).

Features and benefits:

- Adjustable nozzle diameter 0 – 5 mm for spraying with different spray patterns (orange peel effect).
- Equipped with a thread that fits directly on (almost all) 1 liter cans.
- Made out of high quality materials. Well-balanced in use. Robust construction

Application:

Application of soundproof and protective products.

Preparation and Application:

A manual is enclosed with the product. Read the recommendations and instructions of the manual carefully. The manual gives important information regarding the safety of use.

Carefully read and implement the technical information of the products (undercoating) before use. Always wear gloves, goggles and masks with activated carbon filters to avoid risks caused by toxic vapors or by contact of products and solvents with the skin or eyes.

Operation

1. Screw the 1 liter can with threaded ring nut to the support **(9)** as far as it will go.
2. Connect the compressed air supply hose to the connector on the spray gun.
3. Work the lever **(4)** until the product comes out.
4. Adjust the volume coming out using the front regulator **(6)**.
5. To mount the cavity spray hose, first unscrew the front part **(6, 7, 8)** and screw on the spray hose with fitting.

Technical Specification:

Materials:	Nickel-plated aluminium / Nickel-plated Brass
Packaging Unit:	1 pieces per carton box
Operating Temperature	-10°C (253°K), +90°C (343°K)
Thread:	Gun body: 1/4FM BSP Cylindrical gas thread Threaded feed cup fitting: "European" threaded fitting Ø40 (on demand "US Type" Ø45)
Operating Pressure	From 2 Bar/29psi to 8 Bar/116 psi
Air consumption	From 136 L/min (4.82 cfm) to 428 L/min (15.14 cfm)
Net Weight	0,420 kg (0,927 lb)
Dimensions	230 x 275 x 50

Related products of Colad

Article number: 4010 – Colad Undercoating M80 Black
Article number: 4020 – Colad Undercoating M80 White
Article number: 4030 – Colad Undercoating M80 Grey

Disclaimer

Technical Data Sheet & Material Safety Data Sheet; it is the responsibility of the user to read understands and apply the information of the TDS. The information about work and environmental safety is available on the material safety data sheet (MSDS) via www.colad.co. It is the responsibility of the user to read and apply the information.

Products are for professional use. Necessary protective equipment and clothing should be worn. The repairs should always be done in accordance with the OEM rules and specifications. All information is for the user's consideration, investigation and verification. The specific use applications and conditions of use are beyond the control of EMM International B.V. It is the responsibility of the user to determine the suitability of any of the products mentioned for the user's specific application.

Created by:

EMM International BV
Bohemenstraat 19, 8028 SB Zwolle, The Netherlands
www.emm.com



T +31(0)38 467 66 00
www.colad.co