




Technical Data Sheet

<p>General</p> <p>Article number: 6340</p> <p>Description : Colad Masking Film (3,8 m x 200 m)</p>	
<p>Specifications</p> <p>Form: Film on roll. Material: Polyethylene Color: Green transparent. Film width x length: 3,8 meter x 200 meter. Roll width: 95 cm. Odor: Odorless. Temperature resistance: App. 120 °C. Decomposition temperature: > 300 °C. Solubility in water: Insoluble. Relative density: 910 – 990 kg/m³. Auto ignition temperature: > 350 °C. Properties: Static - the film 'clings' to the surface. Absolutely silicone free. Packaging: Per roll in a carton box, 60 carton boxes per pallet. Carton box can be used as a dispenser.</p>	
<p>Application</p> <p>Colad products are worked up and designed for use in car body shops. The Masking Films are ideal for quick and efficient covering of a vehicle and protect it against overspray, dirt and dust. Colad Masking Film is a green translucent masking film without paint adhesion. This film has static properties and is easy to cut with art.no. 2070 or 2075. Colad Masking Film is suitable for use in zones with explosion danger, also in spray booth. By using the Colad Mobile Foil Dispenser (Art.no. 2060) covering can be done by one person. Colad Masking Film is environmentally friendly and can be recycled, safely incinerated or buried in the ground.</p> <p>Used for:</p> <ul style="list-style-type: none"> • Sanding • Light overspray <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>High static power</p> </div> <div style="text-align: center;">  <p>High tensile strength</p> </div> </div> <p>The Colad assortment has a complete range of Masking Film for quick and efficient masking, together with the 6340300 (3,8 m x 300 m), 6365 (4 m x 300 m), 6375 (4 m x 150 m), 6345 (4 m x 150 m, 17 micron), 6660-5 (5 m x 120 m) and the 6660 (6 m x 100 m) there is a fitted film for every job.</p>	
<p>Created by : E.M.M. International BV Marsweg 59 8013 PE Zwolle The Netherlands</p> <p style="text-align: right;">phone +31 38 4676600 fax +31 38 4676699 www.emm.com</p>	