## APPLICATION OVERVIEW



= suggested main use

 $\square$  = also suitable for

 $\bigcirc$  = limited, preliminary tests are recommended.

Always read the TDS and MSDS. Due to a variety of materials, preliminary tests are recommended. Always follow OEM specifications and instructions when repairing.

		Plastic repair				Glass Repair	Sealants		Metal Repair
	Art. no.	90672258	90672259	90672240	90672241	90673719	90672412	906724xx	90672440
	Product name	2K Plastic Adhesive Super Fast 30 Seconds	2K Plastic Adhesive Fast 1.5 Minutes	2K Plastic Adhesive Medium Fast 3.5 Minutes	2K Plastic Adhesive Slow 5 Minutes	Windscreen Adhesive MS Polymer	Sprayable Seam Sealer MS Polymer	Seam Adhesive MS Polymer	Panel Bonding Adhesive
	Colour	Black	Black	Black	Transparent	Black	Grey	Black, White, Grey	Black
	Content	50 ml	50 ml	50 ml	50 ml	290 ml	310 ml	290 ml	195 ml
	Plastics (various types)	•	•	•	•				
	Thermoplastics A (ABS, PA, PC/PBT, PPO/PA, PET).	•		•	•				
	Thermoplastics B (PPO, PC/ABS, PP/EPDM).	•	•	•					
	Thermoplastics C (PPO, PC/ABS, PP/EPDM)  General Adhesion: limited. Preliminary tests recommended.	0	O	0	0				
n	SMC.		•						
	вмс.	•	•		•				•
materials	Gel Coat.								
Ĕ	PUR-RIM (plastic parts: bumper, spoilers).	•							
10	RTM.	•	•	•	•				•
<u> </u>	Carbon Fiber Reinforced Plastics (CFRP).	•	•	•	•				•
	Metals (various types)						•	•	•
	Metals & Metal Alloys (coated or primed).					_			•
	Cold Rolled Steel.								
	Aluminum.								•
	Galvanized steel.								•
	Wood (various types)							•	
	Glass (various types)					•		•	
	Ceramics (various types)							•	
	Small and quick plastic repairs. Hold parts in position. Basic cosmetic & structural repairs. F.I. Mouldings, bumper tabs, emblems.	•	•						
	Reparation of cracks of 0 - 5 cm.		•						
<u> </u>	Small and medium sized plastic repairs. Structural & cosmetic. F.I. Bumpers, panel clips, radiator grills, headlights brackets.			•					
<u>5</u>	Reparation of cracks of 5 - 10 cm.								
pplicati	Medium sized plastic repairs. Repair cracks and holes. Bonding and filling. Structural and cosmetic. Fl. holes and cracks in plastic bumpers and spoilers.			•	•				
2	Reparation of holes and cracks of 5 - 12 cm.			•					
2	Bonding windscreens to the car body, wagons and					•			
3	cabins.								
$\exists$	Textured coating & sound insulation.						•		
0	Filler suitable for larger surfaces.						•		
repairs/	Protective layer inside and outside on (car) body welding and construction seams.						•		
	Sealing & bonding.							•	
	Joints & seams.							•	
	General bonding and assembling.						•	•	
	Metal and composite panel bonding.								•
	Panel to frame assembly.								•



