

# Technical Data Sheet

## General

Article number: 8146  
Description: Ice Transparent Peelable Booth Coating



## Remarks:

A transparent, protective coating that forms a strong layer. Protects your lights and windows from overspray and is easy to remove, it simply peels away when you no longer need it.

## Instructions for application

Clean any loose dirt and/or other grease from the surface to be painted. Stir well before use and do not dilute. Apply with spray gun, airless system, brush or paint roller (Airless: nozzle 417, 100-150 bar spray pressure. Spray gun: 2.5 nozzle, 3 bar spray pressure). Recommended coat thickness: 150 micron. Apply liberally until a milky colour is achieved. This will become transparent once dry. Allow to dry at room temperature. Do not apply multiple coats on top of each other. This will reduce its transparency.

## WARNING!

For best results: apply a test area of approximately 12" x 12", wait 24 hours and test that it can be removed effectively.

**Removal:** Remove by peeling off the layer, residue can be removed with warm water or power washer. Heating up the booth can help.

**Maximum usage:** 250 booth cycles or 3 months.

**Humidity advice:** 40 – 60%

To improve peeling properties carefully cut (with a sharp knife) into the outer edges before removing.

## Technical Specification:

Packaging	Can of 5 L
Consumption	4-6 m <sup>2</sup> per liter
Shelf life	1 year after production at 20°C (see expiring date on the can)
Substance	Water base
Color of the coating	Transparent
Drying time totally	6-8 hours (20°C) (reduce drying time with air flow)
Heat resistance	Up to 60°X
Time to use after applying	± 2 hours
Thickness	Minimum at 150 miron
Drying at 20°C/60% RV	Surface at least 12°C and relative humidity maximal 80%
Maximum usage	250 booth cycles or 3 months

**Related products of Colad**

Article number: 8145 – Description: Blizzard White

Article number: 8200 – Description: Dust Control

**Disclaimer**

Technical Data Sheet & Material Safety Data Sheet; it is the responsibility of the user to read understands and apply the information of the TDS. The information about work and environmental safety is available on the material safety data sheet (MSDS) via [www.colad.co](http://www.colad.co). It is the responsibility of the user to read and apply the information.

Products are for professional use. Necessary protective equipment and clothing should be worn.

The repairs should always be done in accordance with the OEM rules and specifications.

All information is for the user's consideration, investigation and verification. The specific use applications and conditions of use are beyond the control of EMM International BV. It is the responsibility of the user to determine the suitability of any of the products mentioned for the user's specific application.

**Created by:**

EMM International BV

Bohemestraat 19, 8028 SB Zwolle, The Netherlands

[www.emm.com](http://www.emm.com)

T +31(0)38 467 66 00

[www.colad.co](http://www.colad.co)