

## Technical Data Sheet

### General:

Article number: 8145

Description: Blizzard White Peelable Booth Coating



### Specification

- Packaging: 10 L can
- Consumption: 6.66m<sup>2</sup> per liter
- Shelf life: 2 Years at 20°C
- Substance: Water based
- Color of the coating: White
- Drying time totally: 6-8 hours (20° C) (reduce drying time with air flow)
- Heat resistance: Up to 60°C
- Time to use after applying: ± 2 hours
- Thickness: 1<sup>st</sup> layer minimum 150 micron  
Additional layers; 65 micron minimum
- Drying at 20°C/60% RV: Surface at least 12°C and relative humidity maximal 80%
- Maximum usage: 500 booth cycles or 6 months

**Remarks:**

A white, protective coating that forms a strong layer on your booth walls. Protects your walls from overspray giving them a bright appearance and is easy to remove, it simply peels away when you no longer need it.

**Instructions for application**

Clean any loose dirt and/or other grease from the surface to be painted. Mask all transparent parts such as lights and windows. Stir well before use and do not dilute. Apply with spray gun, airless system, brush or paint roller (Airless: nozzle 417, 100-150 bar spray pressure. Spray gun: 2.5 nozzle, 3 bar spray pressure). Recommended coat thickness: 150 micron. Allow to dry at room temperature. Recommended number of coats: First coat: 150 micron. Multiple coats can be applied on top of each other (up to a maximum of 6 layers) to achieve maximum whiteness. All extra coats can be applied at a thickness of 65 microns approx.

**WARNING!**

For best results: apply a test area of approximately 12" x 12", wait 24 hours and test that it can be removed effectively.

**Removal**

Remove by peeling off the layer; residue can be removed with warm water or power washer.

**Maximum usage**

500 booth cycles or 6 months.

**Humidity advice**

40 – 60%

**Application sequence**

Mask Windows and Lights – Apply Blizzard white on spray cabin surface – after removal of masking materials use Colad Ice Transparent Peelable Booth coating (Article 8146) for Lights and windows.

**Created by:**

EMM International BV  
The Netherlands  
[www.emm.com](http://www.emm.com)



T +31(0)38 467 66 00  
[www.colad.co](http://www.colad.co)