

First edition date: February 2, 2004 Last revision date: January 26 2015

Number of pages: 1

Technical Data Sheet

General

Article number: 6340300

Description: Colad Masking Film

 $(3.8 \text{ m} \times 300 \text{ m})$



Specifications

Form: Film on roll. Material: Polyethylene Green transparent. Color: Film width x length: 3,8 meter x 300 meter.

Roll width: 95 cm. Odor: Odorless. App. 120 °C. Temperature resistance: Decomposition temperature: > 300 °C. Solubility in water: Insoluble.

Relative density: $910 - 990 \text{ kg/m}^{3}$

Auto ignition temperature: > 350 °C.

Properties: Static - the film 'clings' to the surface.

Absolutely silicone free.

Packaging: Per roll in a carton box, 49 carton boxes per pallet.

Carton box can be used as a dispenser.

Application

Colad products are worked up and designed for use in car body shops. The Masking Films are ideal for quick and efficient covering of a vehicle and protect it against overspray, dirt and dust. Colad Masking Film is a green translucent masking film without paint adhesion. This film has static properties and is easy to cut with art.no. 2070 or 2075. Colad Masking Film is suitable for use in zones with explosion danger, also in spray booth. By using the Colad Mobile Foil Dispenser (Art.no. 2060) covering can be done by one person. Colad Masking Film is environmentally friendly and can be recycled, safely incinerated or buried in the ground.

Used for:

- Sanding
- Light overspray



High static power

High tensile strength

The Colad assortment has a complete range of Masking Film for quick and efficient masking, together with the 6340 (3,8 m x 200 m), 6365 (4 m x 300 m), 6375 (4 m x 150 m), 6345 (4 m x 150 m, 17 micron), 6660-5 (5 m x 120 m) and the 6660 (6 m x 100 m) there is a fitted film for every job.

Created by:

E.M.M. International BV Marsweg 59

8013 PE Zwolle The Netherlands phone +31 38 4676600 fax +31 38 4676699 www.emm.com

