



Technical Data Sheet

<p>General</p> <p>Article number: 9067xx (906709, 906712)</p> <p>Description: Colad Seam Sealing Tape</p>																	
<p>Specification:</p> <p>Seam Sealing Tape is a reinforced acrylic tape with acrylic adhesive that has high tack and shear strength performance. Excellent resistance to solvent, chemical, UV and heat makes the tape bond securely to a very wide range of substrates. Two variants – 9 mm and 12 mm – for perfect sealing. Ideal for reviving older sealings and/or paint preparation on automotive doors and angles. A time saver for applying sealing seams for paint projects on car, truck and camper doors and angles. Replace old seams with new ones. Just apply the new seam on the spot, paint the object, dry the paint and you're done. A real time saver!</p> <p>Features and benefits:</p> <ul style="list-style-type: none"> • Ideal for renewing sealing seams on automotive doors and angles • Easy to use and to apply • Immediately paintable – no need for an adhesion promoter • Time saving compared to liquid sealers • Excellent resistance to solvents, chemicals, UV and heat • Flat profile; tacks very well to all smooth surfaces and is easy shapeable to the object • Flexible for applying on doors and angles • Easy removable without leaving any residue <p>Application:</p> <p>The product can be applied in between seems to create a permanent seal. Application on a prepared and degreased surface. Remove the liner after application so that it is immediately ready to paint. No need to prepare the surface of the tape for the basecoat.</p>																	
<p>Technical Specification:</p> <table border="1"> <tr> <td>Colour</td> <td>white</td> </tr> <tr> <td>Roll length</td> <td>9 m</td> </tr> <tr> <td>Roll diameter (Ø)</td> <td>14 cm</td> </tr> <tr> <td>Width roll</td> <td>906709 - 9 mm 906712 - 12 mm</td> </tr> <tr> <td>Roll weight</td> <td>906709 – 100 g 906712 – 131 g</td> </tr> <tr> <td>Packaging Unit</td> <td>906709: Per roll / 140 rolls per box 906712: Per roll / 100 rolls per box</td> </tr> <tr> <td>Storage</td> <td>Preferred temperature 20-25°C</td> </tr> <tr> <td>Shelf Life</td> <td>One year from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.</td> </tr> </table>		Colour	white	Roll length	9 m	Roll diameter (Ø)	14 cm	Width roll	906709 - 9 mm 906712 - 12 mm	Roll weight	906709 – 100 g 906712 – 131 g	Packaging Unit	906709: Per roll / 140 rolls per box 906712: Per roll / 100 rolls per box	Storage	Preferred temperature 20-25°C	Shelf Life	One year from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.
Colour	white																
Roll length	9 m																
Roll diameter (Ø)	14 cm																
Width roll	906709 - 9 mm 906712 - 12 mm																
Roll weight	906709 – 100 g 906712 – 131 g																
Packaging Unit	906709: Per roll / 140 rolls per box 906712: Per roll / 100 rolls per box																
Storage	Preferred temperature 20-25°C																
Shelf Life	One year from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.																

Physical properties:

Carrier: Acrylic foam base in clear carrier
Liner: Kraft paper
Adhesive: High tack acrylic (solvent based)
Thickness: 0.5 mm and 1 mm (± 0.05 mm)
Width: 9 mm and 12 mm (± 1 mm)
Length: 9 m (± 0.1 m)

Release liner



Acrylic carrier

Adhesive

Performance properties:

Peel adhesion: PSTC-3 2.8 kg/25 mm
Shear adhesion: PSTC-7 over 72 hours with 2 kg on 25 mm x 25 mm at 25°C
Tensile strength: Over 50 kg/25 mm x 25 mm
Heat resistance: PSTC-9 over 24 hours with 1 kg on 25 mm x 25 mm at 80°C
Service temperature: -40°C to 170°C
Application temperature: -10°C to 150°C

Related products of Colad:

Article number: 53200x – Description: Polyester Preparation Gloves

FAQ:

Q1: Do I need an adhesion promoter before painting?

A1: No. Once in place, you can start painting immediately.

Q2: How do I remove the Seam Sealing Tape?

A2: Just stretch the tape and you can remove it.

Disclaimer:

Technical Data Sheet & Material Safety Data Sheet; it is the responsibility of the user to read understands and apply the information of the TDS. The information about work and environmental safety is available on the material safety data sheet (MSDS) via www.colad.co. It is the responsibility of the user to read and apply the information.

Products are for professional use. Necessary protective equipment and clothing should be worn.

The repairs should always be done in accordance with the OEM rules and specifications.

All information is for the user's consideration, investigation and verification. The specific use applications and conditions of use are beyond the control of EMM International BV. It is the responsibility of the user to determine the suitability of any of the products mentioned for the user's specific application.

Created by:

EMM International BV
Bohemenstraat 19, 8028 SB Zwolle, The Netherlands
www.emm.com

T +31(0)38 467 66 00
www.colad.co